

Title (en)

Process for pickling stainless steel.

Title (de)

Verfahren zum Beizen von Edelstahl.

Title (fr)

Procédé de décapage de l'acier inoxydable.

Publication

**EP 0471662 B1 19950913 (DE)**

Application

**EP 91890156 A 19910717**

Priority

AT 157990 A 19900727

Abstract (en)

[origin: US5130000A] Process for pickling high-grade steel, preferably high-grade steel hot strip, the high-grade steel being subjected to pickling with neutral electrolyte as well as to an after-treatment with mixed acid, nitric acid or a mixture of iron fluoride and hydrofluoric acid, the pickling with neutral electrolyte being preceded by a pre-treatment with sulfuric acid.

IPC 1-7

**C25F 1/06**

IPC 8 full level

**C23G 1/08** (2006.01); **C23F 1/00** (2006.01); **C23F 1/28** (2006.01); **C25F 1/06** (2006.01)

CPC (source: EP KR US)

**C25F 1/06** (2013.01 - EP KR US)

Cited by

AT402737B

Designated contracting state (EPC)

AT BE DE ES FR GB IT NL SE

DOCDB simple family (publication)

**EP 0471662 A2 19920219; EP 0471662 A3 19920520; EP 0471662 B1 19950913;** AT 395601 B 19930225; AT A157990 A 19920615; AT E127866 T1 19950915; DE 59106467 D1 19951019; ES 2079634 T3 19960116; JP 2721053 B2 19980304; JP H04232299 A 19920820; KR 100218840 B1 19990901; KR 920002826 A 19920228; RU 2085616 C1 19970727; UA 25894 A1 19990226; US 5130000 A 19920714; ZA 915877 B 19920429

DOCDB simple family (application)

**EP 91890156 A 19910717;** AT 157990 A 19900727; AT 91890156 T 19910717; DE 59106467 T 19910717; ES 91890156 T 19910717; JP 18450891 A 19910724; KR 910012248 A 19910718; SU 5001185 A 19910726; UA 5001185 A 19910726; US 73281791 A 19910719; ZA 915877 A 19910726