

Title (en)  
INDUCTION SKULL MELT SPINNING OF REACTIVE METAL ALLOYS

Publication  
**EP 0471798 B1 19930623 (EN)**

Application  
**EP 90911041 A 19900430**

Priority  
US 34525489 A 19890501

Abstract (en)  
[origin: WO9013377A1] An apparatus for melting and rapid solidification casting of metal alloys has a crucible (2) for molding a metal charge. The crucible has side walls (3), a top (7) and a bottom (20) having an orifice (5) therein. Collectively, the side walls, top and bottom define an interior of the crucible. A portion of the dimensions of the side walls and bottom is divided by longitudinal slits (11) into at least two segments. A nozzle (8) is disposed partially within the crucible and extends through the orifice. The nozzle has a first end (24) in communication with the interior (22) of the crucible. A second end (26) of the nozzle has a nozzle orifice (28) therein for defining a stream of molten metal alloy. A cooling mechanism (4) cools the top, side walls and bottom of the crucible. The apparatus has mechanisms (30, 32, 34) for inducing alternating electrical currents within the metal charge and within the nozzle, and for establishing and maintaining pressure within the interior of the crucible. A positioning mechanism (10) positions the crucible and nozzle means relative to a quenching mechanism (36) that includes a rapidly moving chill substrate. The crucible, nozzle and quenching mechanism are housed within an enclosure (1) that provides therewithin a controlled atmosphere having positive or negative pressure.

IPC 1-7  
**B22D 11/06**

IPC 8 full level  
**B22D 11/06** (2006.01)

CPC (source: EP)  
**B22D 11/064** (2013.01)

Cited by  
US5272718A

Designated contracting state (EPC)  
DE FR GB

DOCDB simple family (publication)  
**WO 9013377 A1 19901115**; DE 69002059 D1 19930729; DE 69002059 T2 19930930; EP 0471798 A1 19920226; EP 0471798 B1 19930623; JP 3054193 B2 20000619; JP H04504981 A 19920903

DOCDB simple family (application)  
**US 9002387 W 19900430**; DE 69002059 T 19900430; EP 90911041 A 19900430; JP 51044590 A 19900430