

Title (en)
High-temperature superconductive conductor winding.

Title (de)
Hochtemperatur-supraleitende Spule.

Title (fr)
Bobine supra-conductrice à haute température.

Publication
EP 0472197 A1 19920226 (EN)

Application
EP 91114090 A 19910822

Priority
JP 22348190 A 19900824

Abstract (en)
In a high-temperature superconductive conductor winding (1) comprising a tape-type high-temperature superconducting wire (2) which is combined with a metal and wound into the form of a double pancake coil, the length of a throughout portion (5) provided between pancakes (4, 6) is at least four times the width of the tape-type high-temperature superconducting wire. Thus, it is possible to suppress generation of shearing stress at the throughout portion (5), thereby preventing reduction of the critical current density caused by such shearing stress. <IMAGE>

IPC 1-7
H01F 7/22

IPC 8 full level
H01F 6/06 (2006.01)

CPC (source: EP)
H01F 6/06 (2013.01)

Citation (search report)

- [A] US 3281737 A 19661025 - SWARTZ PAUL S
- [A] US 3813764 A 19740604 - FUKUDA T, et al
- [A] EP 0045604 A2 19820210 - MITSUBISHI ELECTRIC CORP [JP], et al
- [A] US 4499443 A 19850212 - MATERNA PETER A [US]

Cited by
EP1096580A4; EP0724273A3; US5604473A; US5581220A; FR2895802A1; US2013172196A1; US9048015B2; US7855628B2; US7952454B2; WO2005087532A1; WO0052781A1; WO0157888A1; EP1829062B1; WO2007077383A1; WO2012031790A1; EP0786141B2

Designated contracting state (EPC)
DE FR GB

DOCDB simple family (publication)
EP 0472197 A1 19920226; EP 0472197 B1 19941221; DE 69106080 D1 19950202; DE 69106080 T2 19950518; JP 3309390 B2 20020729; JP H04106906 A 19920408

DOCDB simple family (application)
EP 91114090 A 19910822; DE 69106080 T 19910822; JP 22348190 A 19900824