

Title (en)  
SPOUT ASSEMBLY AND SEALING CAP WITH SPRING-LOADED HINGE.

Title (de)  
AUSGIESS- UND VERSCHLUSSEINHEIT MIT SCHNAPPSCHARNIER.

Title (fr)  
ENSEMBLE VERSEUR ET CAPSULE DE BOUCHAGE AVEC CHARNIERE A RESSORT.

Publication  
**EP 0472655 A1 19920304 (FR)**

Application  
**EP 90908957 A 19900517**

Priority  
• FR 8906433 A 19890517  
• FR 9000346 W 19900517

Abstract (en)  
[origin: US5301849A] PCT No. PCT/FR90/00346 Sec. 371 Date Nov. 12, 1991 Sec. 102(e) Date Nov. 12, 1991 PCT Filed May 17, 1990 PCT Pub. No. WO90/14287 PCT Pub. Date Nov. 29, 1990. A spout and sealing cap assembly for a container which includes a spout which is connectable to the container, a sealing cap for closing off a dispensing opening in the spout and a bi-stable hinge integrally formed with the sealing cap. The bi-stable hinge maintains the cap only in one of two stable positions, an open position and a closed position. The spout is formed as a first one-piece plastic part with an undercut profile connection portion. The sealing cap is also formed as a second one-piece plastic part with an undercut profile connection portion spaced from the bi-stable hinge. The plastic of the spout is a formed of a more flexible plastic than that of the sealing cap. The bi-stable hinge is formed integrally with the sealing cap and, thus, also is formed of the relatively rigid, hard plastic. The first and second undercut profile connection portions are interconnected in an interconnection arrangement resulting from an over-molding of the second one-piece elastic part over the first one-piece plastic part. In one embodiment, the sealing cap includes an extension extending from the hinge and having a free edge with an undercut for connection with a corresponding extension of the spout.

Abstract (fr)  
Ensemble verseur et capsule de bouchage comprenant un corps verseur destiné à être fixé à un récipient et une capsule de bouchage destinée à obturer le corps verseur et reliée au corps verseur par une charnière à ressort, caractérisé par le fait que le corps verseur (1) est réalisé en matière plastique souple, par moulage, et que la capsule (2) est réalisée d'une seule pièce avec la charnière (3) par surmoulage du corps verseur, en matière plastique dure.

IPC 1-7  
**B65D 47/08**

IPC 8 full level  
**B65D 47/08** (2006.01)

CPC (source: EP US)  
**B65D 47/0814** (2013.01 - EP US)

Citation (search report)  
See references of WO 9014287A1

Cited by  
FR2888565A1; WO2007006954A1; WO2007006957A1

Designated contracting state (EPC)  
AT BE CH DE DK ES FR GB IT LI LU NL SE

DOCDB simple family (publication)  
**US 5301849 A 19940412**; AT E107254 T1 19940715; AU 5747090 A 19901218; AU 631432 B2 19921126; CA 2057906 A1 19901118; DE 69010003 D1 19940721; DE 69010003 T2 19940922; DK 0472655 T3 19941107; EP 0472655 A1 19920304; EP 0472655 B1 19940615; ES 2055434 T3 19940816; FR 2647088 A1 19901123; FR 2647088 B1 19911122; GR 1003022 B 19981203; GR 900100376 A 19911010; JP H05500002 U 19930204; NO 179939 B 19961007; NO 179939 C 19970115; NO 914499 D0 19911118; NO 914499 L 19911118; PT 94061 A 19910108; PT 94061 B 19970430; WO 9014287 A1 19901129; ZA 903791 B 19910327

DOCDB simple family (application)  
**US 77724091 A 19911112**; AT 90908957 T 19900517; AU 5747090 A 19900517; CA 2057906 A 19900517; DE 69010003 T 19900517; DK 90908957 T 19900517; EP 90908957 A 19900517; ES 90908957 T 19900517; FR 8906433 A 19890517; FR 9000346 W 19900517; GR 900100376 A 19900516; JP 60001591 U 19900517; NO 914499 A 19911118; PT 9406190 A 19900516; ZA 903791 A 19900517