

Title (en)

Arrangement to limit the terminal voltage in an alternator.

Title (de)

Einrichtung zur Begrenzung der Klemmenspannung bei einer Drehstromlichtmaschine.

Title (fr)

Dispositif pour limiter la tension aux bornes d'un alternateur triphasé.

Publication

EP 0472805 B1 19941012 (DE)

Application

EP 91103494 A 19910307

Priority

DE 4016573 A 19900523

Abstract (en)

[origin: US5187426A] An arrangement for limiting the terminal voltage in an alternator has a fixed stator winding acting on rectifiers and an excitation winding which rotates with the alternator rotor. The arrangement also has a controller and a first slip ring contact which load the excitation winding with excitation current as a function of the magnitude of a delivered voltage, and at least one free-wheeling valve which is conductive during a controller-side interruption of the excitation current and is connected in parallel with the excitation winding. The arrangement includes an auxiliary winding on the rotor. The auxiliary winding continues the excitation winding in the same direction of winding, with the auxiliary winding and the excitation winding being connected at a first connection point. A second slip ring contact operatively connects the first connection point to a machine terminal supplying excitation current. A zener diode is connected in series with auxiliary winding, and a third slip ring contact operatively connects the auxiliary winding to a ground terminal of the alternator or of the controller.

IPC 1-7

H02H 9/04; H02H 7/06; H02J 7/16

IPC 8 full level

H02H 7/06 (2006.01); **H02H 9/04** (2006.01); **H02P 9/10** (2006.01); **H02P 9/14** (2006.01); **H02P 9/30** (2006.01)

CPC (source: EP US)

H02H 7/067 (2013.01 - EP US); **H02H 9/047** (2013.01 - EP US); **H02P 9/107** (2013.01 - EP US)

Designated contracting state (EPC)

AT CH FR IT LI SE

DOCDB simple family (publication)

US 5187426 A 19930216; AT E112902 T1 19941015; DE 4016573 C1 19910829; EP 0472805 A2 19920304; EP 0472805 A3 19920916; EP 0472805 B1 19941012; JP H05276800 A 19931022; JP H0681560 B2 19941012

DOCDB simple family (application)

US 68637591 A 19910417; AT 91103494 T 19910307; DE 4016573 A 19900523; EP 91103494 A 19910307; JP 14393491 A 19910520