

Title (en)

Protector plug for distributor board of telephonic equipments, in particular for private branch exchanges.

Title (de)

Schutzstecker für eine in Telekommunikations-, insbesondere Fernsprechnebenstellenanlagen eingesetzte Verteilerleiste.

Title (fr)

Insert de protection pour réglette à bornes installée dans un équipement de télécommunication, en particulier dans un poste annexe téléphonique.

Publication

EP 0477664 B1 19941130 (DE)

Application

EP 91115365 A 19910911

Priority

DE 4030781 A 19900928

Abstract (en)

[origin: EP0477664A1] The housing of the protector plug, in which an overvoltage suppressor (28) is arranged, consists of a base-like lower part (2) and an upper part which is integrally connected to it via a film hinge. The upper part preferably consists of two halves (3, 4) which are pivoted with respect to one another to close the protector plug housing and are mechanically connected to one another by suitable locking elements. The lower part (2) contains retaining chambers (8) for contact parts which have a double spring contact emerging downwards from a base part in the plug-in direction, and a terminal connection emerging upwards therefrom. There are three identical contact parts (19) which are each connected via their terminal connections (21) to the connecting pins (29) of the overvoltage suppressor (28). The pin-shaped projections (35-37), which protrude from a distribution board (38), are used as mating contacts for the double spring contacts (25). The contact element (19) has an offset between the centre line of the double spring contact (25) and the actual connection of the connecting legs (29) of the overvoltage suppressor (28), which are located in a line. In the case of retaining chambers which are arranged offset with respect to one another, the overvoltage suppressor can be inserted in a straight line without deformation of its connecting legs in a manner matched thereto, if the individual contact elements are fitted into the retaining chamber in a specific position, rotated with respect to one another. <IMAGE>

IPC 1-7

H01R 4/48; **H01T 4/06**

IPC 8 full level

H01R 4/48 (2006.01); **H01R 9/24** (2006.01); **H01R 13/50** (2006.01); **H01T 4/06** (2006.01)

CPC (source: EP US)

H01R 9/2441 (2013.01 - EP US); **H01R 13/501** (2013.01 - EP US); **H01T 4/06** (2013.01 - EP US)

Cited by

EP0623976A3

Designated contracting state (EPC)

BE CH DE FR GB IT LI SE

DOCDB simple family (publication)

EP 0477664 A1 19920401; **EP 0477664 B1 19941130**; CA 2052325 A1 19920329; CA 2052325 C 20020521; DE 59103665 D1 19950112; US 5154639 A 19921013

DOCDB simple family (application)

EP 91115365 A 19910911; CA 2052325 A 19910926; DE 59103665 T 19910911; US 76638791 A 19910927