

Title (en)

Method of producing permalloy cores.

Title (de)

Verfahren zur Herstellung von Kernen aus Permalloy.

Title (fr)

Procédé de fabrication d'âmes en permalloy.

Publication

**EP 0480265 A1 19920415 (EN)**

Application

**EP 91116547 A 19910927**

Priority

- JP 26580390 A 19901003
- JP 26580490 A 19901003

Abstract (en)

A method of producing permalloy cores comprising the steps of applying an annealing separator coating 0.1 to 50  $\mu\text{m}$  thick to at least one surface of wide permalloy strip, slitting the wide permalloy strip to a final width, winding or punching the final width strip, and annealing the strip at a temperature in the range 1000 DEG to 1300 DEG C, and a permalloy core producible with this method. The method allows the efficient manufacturing of permalloy cores with highly stable magnetic properties.

IPC 1-7

**C21D 1/70**; **H01F 41/02**

IPC 8 full level

**C21D 1/70** (2006.01); **H01F 41/02** (2006.01)

CPC (source: EP)

**C21D 1/70** (2013.01); **H01F 41/0206** (2013.01)

Citation (search report)

- [A] EP 0337716 A2 19891018 - MITSUI PETROCHEMICAL IND [JP]
- [A] DE 4002999 A1 19900816 - HITACHI METALS LTD [JP]
- [A] EP 0057983 A2 19820818 - ALLEGHENY LUDLUM STEEL [US]
- [A] CHEMICAL ABSTRACTS, vol. 111, no. 4, 24 July 1989, Columbus, Ohio, US; abstract no. 32474J, Y. SATO: 'HIGH ELECTRICAL INSULATION-INTERLAYER COATING METHOD USING MAGNESIUM HYDROXIDE FOR TAPE WOUND MAGNETIC CORES OF HIGH PERMABILITY NICKEL IRON ALLOYS' page 616 ;column 1 ;

Cited by

DE19754996A1; DE19754996C2

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**EP 0480265 A1 19920415**; **EP 0480265 B1 19950517**; DE 69109794 D1 19950622; DE 69109794 T2 19960208

DOCDB simple family (application)

**EP 91116547 A 19910927**; DE 69109794 T 19910927