

Title (en)

DEVICE FOR DISPENSING A MIXTURE CONSISTING OF AT LEAST TWO COMPONENTS

Publication

EP 0482319 B1 19931013 (DE)

Application

EP 91114634 A 19910830

Priority

CH 342690 A 19901026

Abstract (en)

[origin: EP0482319A1] The device comprises a first chamber (1), which is formed by a container (4), and a second chamber (2) which is formed by a cylinder (8) and two tightly displaceable covering parts (9, 10). The covering parts (9, 10) are connected to an element (17) which is guided out through the closure part (19) of the discharge valve (7). By pulling on this element (17), the second chamber (2) with the second component is displaced relative to the cylinder (8) and first chamber (1) until the second component has forcibly been conveyed out of the cylinder (8). <??>The advantage of this arrangement is that the use of the device is independent of the components and the second component is introduced completely into the first component. <IMAGE>

IPC 1-7

B65D 81/32; B65D 83/14

IPC 8 full level

B65D 81/32 (2006.01); **B65D 83/00** (2006.01); **B65D 83/14** (2006.01)

CPC (source: EP US)

B65D 81/3222 (2013.01 - EP US); **B65D 83/22** (2013.01 - EP US); **B65D 83/303** (2013.01 - EP US); **B65D 83/687** (2013.01 - EP US)

Cited by

US5549226A; DE4313319B4; GB2298180A; GB2298180B; WO2007042013A1; WO9618556A1; US11161674B2; WO2019102025A1; WO0035758A3

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0482319 A1 19920429; EP 0482319 B1 19931013; AT E95790 T1 19931015; CH 683515 A5 19940331; DE 59100487 D1 19931118; DK 0482319 T3 19940314; ES 2044668 T3 19940101; JP 2938249 B2 19990823; JP H0811945 A 19960116; US 5215225 A 19930601

DOCDB simple family (application)

EP 91114634 A 19910830; AT 91114634 T 19910830; CH 342690 A 19901026; DE 59100487 T 19910830; DK 91114634 T 19910830; ES 91114634 T 19910830; JP 29845091 A 19911016; US 76605191 A 19910926