

Title (en)

Lock for automobile safety belt.

Title (de)

Schloss für Sicherheitsgurtsysteme in Fahrzeugen.

Title (fr)

Fermeture pour ceinture de sécurité de véhicules automobiles.

Publication

**EP 0485656 B1 19950510 (DE)**

Application

**EP 90121893 A 19901115**

Priority

EP 90121893 A 19901115

Abstract (en)

[origin: EP0485656A1] In a lock for safety-belt systems in vehicles which are equipped with tautening devices engaging on the lock, an automatic opening is prevented by a two-armed lever (42) which is mounted pivotably on the load-bearing housing (10). During each actuation of the release button (32), the lever is pivoted out of its position of rest into a deflected position. At the end of a tautening movement, one (44) of the arms of the lever (42) projects into the path of movement of the release button (32), in order to prevent its further movement in the actuating direction. <IMAGE>

IPC 1-7

**A44B 11/25**

IPC 8 full level

**A44B 11/25** (2006.01)

CPC (source: EP US)

**A44B 11/2523** (2013.01 - EP US); **Y10T 24/45623** (2015.01 - EP US); **Y10T 24/4567** (2015.01 - EP US)

Cited by

EP0723747A3; EP0820708A3; EP0679348A3; US6363591B1; EP1025774A3; FR2687965A1; US6266855B1; WO9907243A1

Designated contracting state (EPC)

DE ES FR GB IT SE

DOCDB simple family (publication)

**EP 0485656 A1 19920520**; **EP 0485656 B1 19950510**; DE 59009070 D1 19950614; ES 2032369 T1 19930216; ES 2032369 T3 19950916; JP H04266706 A 19920922; JP H0651007 B2 19940706; US 5213365 A 19930525

DOCDB simple family (application)

**EP 90121893 A 19901115**; DE 59009070 T 19901115; ES 90121893 T 19901115; JP 29922291 A 19911114; US 79037591 A 19911112