

Title (en)
OVERLOAD PROTECTION FOR MECHANICAL PRESS

Publication
EP 0485755 A3 19920930 (DE)

Application
EP 91117706 A 19911017

Priority
DE 4036470 A 19901115

Abstract (en)
[origin: EP0485755A2] An overload protection system for a mechanically driven press is proposed which utilises the maximum press force, i.e. the nominal press force, in the ram even with very irregular loading of the drive fittings, without the overload protection system becoming active beforehand. This occurs according to the invention in that a higher force acting on one drive fitting is compensated by a corresponding application of force on the other drive fitting. For this purpose, it is necessary to generate on the side of the press ram with a reduced effective force a corresponding additional force by the application of pressure. This additional force is generated by an additional, controllable pressure pad (22), the additional force generated being of such a size that the pressure-overloading valve is released when the maximum permissible nominal press force is exceeded. <IMAGE>

IPC 1-7
B30B 15/28

IPC 8 full level
B30B 15/28 (2006.01)

CPC (source: EP)
B30B 15/281 (2013.01); **B30B 15/284** (2013.01)

Citation (search report)
• [A] DE 2331697 B1 19740822
• [AD] DE 1577206 A1 19700409 - KRUPP GMBH
• [A] FR 2075436 A5 19711008 - WEINGARTEN AG MASCHF
• [A] DE 1288431 B 19690130 - WEINGARTEN AG MASCHF
• [A] EP 0114170 A1 19840801 - SCHULER GMBH L [DE]
• [A] PATENT ABSTRACTS OF JAPAN vol. 11, no. 393 (M-654)(2840) 23. Dezember 1987 & JP-A-62 161 500 (AIDA ENG. LTD.) 17. Juli 1987

Cited by
US5638748A; EP0722793A3

Designated contracting state (EPC)
DE ES FR GB IT

DOCDB simple family (publication)
EP 0485755 A2 19920520; EP 0485755 A3 19920930; EP 0485755 B1 19941214; DE 4036470 A1 19920521; DE 59103895 D1 19950126; ES 2067831 T3 19950401

DOCDB simple family (application)
EP 91117706 A 19911017; DE 4036470 A 19901115; DE 59103895 T 19911017; ES 91117706 T 19911017