

Title (en)

CATCH DEVICE FOR POSITIONING BAR OF PAPER PUNCHES

Publication

EP 0487545 B1 19931006 (DE)

Application

EP 90910714 A 19900706

Priority

DE 3926835 A 19890814

Abstract (en)

[origin: WO9102635A1] A catch spring for a positioning bar (14) which is slidably arranged in a punch base (32) and provided with a plurality of spaced catch recesses (12) is constructed as a one-piece spring clip (10) made of flexible strip material. It consists of a spring strip (16), which is convex on the side nearer the positioning bar (14) and which is provided with central catch cams (26), and two spring legs (10) arranged on the ends of the spring strip (16) arranged one behind the other in the direction of motion of the positioning bar (14) after the side facing the positioning bar (14). The spring legs (10) are bent symmetrically through the same angle and their free ends are mounted on the punch base (32) so that they cannot slide or tilt.

IPC 1-7

B26F 1/36

IPC 8 full level

B26D 7/01 (2006.01); **B26F 1/32** (2006.01); **B26F 1/36** (2006.01)

CPC (source: EP KR)

B26F 1/36 (2013.01 - EP KR)

Designated contracting state (EPC)

AT CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)

WO 9102635 A1 19910307; CN 1019769 B 19921230; CN 1049472 A 19910227; DD 297108 A5 19920102; DE 59003033 D1 19931111; EP 0487545 A1 19920603; EP 0487545 B1 19931006; ES 2045936 T3 19940116; JP H04503633 A 19920702; KR 920700861 A 19920810

DOCDB simple family (application)

EP 9001093 W 19900706; CN 90106971 A 19900814; DD 34343990 A 19900814; DE 59003033 T 19900706; EP 90910714 A 19900706; ES 90910714 T 19900706; JP 51066490 A 19900706; KR 910701522 A 19911105