

Title (en)  
FUEL-INJECTION VALVE.

Title (de)  
BRENNSTOFFEINSPRITZVENTIL.

Title (fr)  
SOUPAPE D'INJECTION DE CARBURANT.

Publication  
**EP 0489124 B1 19950111 (DE)**

Application  
**EP 91909756 A 19910604**

Priority  
• DE 9100469 W 19910604  
• DE 4019752 A 19900621

Abstract (en)  
[origin: WO9119900A1] Prior art fuel-injection valves have a cup-shaped protective cap with a recess extending radially outwards from the cap. Together with the injection valve, the recess forms a gap which is small enough to exert a capillary effect on the fuel so that, when the engine is turned off, the high-boiling components of the fuel are deposited at the outer edge of the gap and the injection apertures stay free of deposits. The protective cap (20) proposed by the invention has at least three protuberances (30) integral with the bottom (28) of the cap, the protuberances projecting out a given longitudinal distance (31) towards the injection valve and abutting the orifice plate (15) of the valve. A longitudinal gap (36) of defined width is thus formed by simple means between the floor (28) of the cap and the aperture plate (15). The protective cap disclosed can be used in various types of fuel-injection valve.

IPC 1-7  
**F02M 61/18**

IPC 8 full level  
**F02M 61/16** (2006.01); **F02M 61/18** (2006.01)

CPC (source: EP US)  
**F02M 61/168** (2013.01 - EP US); **F02M 61/1853** (2013.01 - EP US)

Designated contracting state (EPC)  
DE ES FR GB IT

DOCDB simple family (publication)  
**WO 9119900 A1 19911226**; AU 627979 B2 19920903; AU 7890691 A 19920107; DE 4019752 A1 19920102; DE 59104245 D1 19950223; EP 0489124 A1 19920610; EP 0489124 B1 19950111; ES 2067232 T3 19950316; JP 3193042 B2 20010730; JP H05500407 A 19930128; US 5273215 A 19931228

DOCDB simple family (application)  
**DE 9100469 W 19910604**; AU 7890691 A 19910604; DE 4019752 A 19900621; DE 59104245 T 19910604; EP 91909756 A 19910604; ES 91909756 T 19910604; JP 50918491 A 19910604; US 83424492 A 19920219