

Title (en)

Method of detecting a deflated tyre on a vehicle.

Title (de)

Verfahren zur Feststellung eines leeren Reifens an einem Fahrzeug.

Title (fr)

Méthode de détection du dégonflage d'un pneumatique sur un véhicule.

Publication

EP 0489563 B1 19940608 (EN)

Application

EP 91311222 A 19911203

Priority

GB 9026558 A 19901206

Abstract (en)

[origin: EP0489563A1] A method of detecting a deflated tyre on a vehicle by comparing the rolling radii of the tyres by means of comparing angular velocity signals from wheel speed sensors at each wheel characterised by calculating the factors C_1, C_2, C_3 and C_4 are the signals for the speeds of the front left-hand, front right-hand, rear left-hand and rear right-hand wheels of the vehicle, monitoring these factors and if the value of one or more factor becomes greater than 1.0005 or less than 0.9995 producing a warning signal to indicate that a tyre has become partially or completely deflated.

IPC 1-7

B60C 23/00

IPC 8 full level

B60C 23/06 (2006.01)

CPC (source: EP US)

B60C 23/061 (2013.01 - EP US)

Cited by

US6831553B2; DE10152590A1; DE4331845B4; EP0656268A4; US5591906A; DE19619393B4; DE4339970B4; FR3067289A1; RU2760044C2; EP0751019A1; EP1306235A1; GB2281140A; GB2281140B; US5583483A; US6826462B2; US6439045B1; US8180523B2; US6799129B2; WO9852780A1; WO0151298A1; WO2018224780A1

Designated contracting state (EPC)

BE DE ES FR GB IT SE

DOCDB simple family (publication)

EP 0489563 A1 19920610; EP 0489563 B1 19940608; DE 69102403 D1 19940714; DE 69102403 T2 19940929; ES 2055550 T3 19940816; GB 9026558 D0 19910123; JP 3095836 B2 20001010; JP H04262907 A 19920918; US 5252946 A 19931012

DOCDB simple family (application)

EP 91311222 A 19911203; DE 69102403 T 19911203; ES 91311222 T 19911203; GB 9026558 A 19901206; JP 31506491 A 19911129; US 80221591 A 19911204