

Title (en)
MOULDING METHOD

Publication
EP 0489799 A4 19920812 (EN)

Application
EP 90912982 A 19900830

Priority
• AU PJ603789 A 19890830
• AU PJ956490 A 19900410

Abstract (en)
[origin: WO9103363A1] A former (18) is initially moulded to have a relatively thick wall (average about 2mm) with an outer shape forming surface and an inner surface defining a hollow, and a hollow extension (20) which extends from one end, and the shape forming surface has a liquid coagulant (22) applied to it and is subsequently immersed in a liquid latex (25) which sets over the former (18), whereupon the former (18) is evacuated of air and therefore reduces its volume and the relatively thin latex skin (29) (average about 0.25mm thickness) is removed from the former (18).

IPC 1-7
B29C 41/42; **B29C 33/48**

IPC 8 full level
A63H 9/00 (2006.01); **B29C 33/46** (2006.01); **B29C 33/50** (2006.01); **B29C 37/00** (2006.01); **B29C 41/14** (2006.01); **B29C 41/42** (2006.01); **B29C 41/46** (2006.01); **B29C 44/12** (2006.01); **B29D 22/00** (2006.01)

CPC (source: EP)
A63H 9/00 (2013.01); **B29C 33/46** (2013.01); **B29C 33/505** (2013.01); **B29C 37/0017** (2013.01); **B29C 41/14** (2013.01); **B29C 41/42** (2013.01); **B29C 41/46** (2013.01); **B29C 44/12** (2013.01); **B29D 22/00** (2013.01); **B29L 2031/5218** (2013.01)

Citation (search report)
• [A] US 2389009 A 19451113 - TILLOTSON NEIL E
• See references of WO 9103363A1

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB IT LI LU NL SE

DOCDB simple family (publication)
WO 9103363 A1 19910321; EP 0489799 A1 19920617; EP 0489799 A4 19920812

DOCDB simple family (application)
AU 9000388 W 19900830; EP 90912982 A 19900830