

Title (en)

SLIP RING OR COMMUTATOR MOTOR.

Title (de)

SCHLEIFRING- BZW. KOMMUTATORMOTOR.

Title (fr)

MOTEUR A BAGUE OU A COLLECTEUR.

Publication

EP 0489866 A1 19920617 (DE)

Application

EP 90914530 A 19900823

Priority

- DE 8910428 U 19890831
- DE 9011574 U 19900808
- EP 9001409 W 19900823
- EP 89116123 A 19890831

Abstract (en)

[origin: US5329198A] In order to be able to ensure with low outlay a slip ring or commutator motor having a high level of freedom from noise and good running quality at maximum power, despite unavoidable deviations from circularity of the slip ring or commutator ground by the brushes abutting thereon, it is proposed according to the invention that the brushes (6; 7; 8) be supported such that they can pivot about an axis which runs radially in the vicinity of the surface and axially essentially in the axial direction of the commutator (1) or slip ring; that, according to one embodiment, the axis be formed by a guide pin (31; 41), which is retained in a brush housing (2) at least partially embracing the brush (6; 7) in the vicinity of the surface of the commutator (1) or the slip ring, and which is plugged axially through a guide slot (61; 71) running in the compression direction of the brush and open towards the surface of the slip ring or commutator (1), or that the brush (6) be tangentially embraced externally by the brush compression spring (3a) in the sense of a support with tangential supporting parts (33a; 34a), which can pivot.

Abstract (fr)

Pour assurer un fonctionnement silencieux et sans à-coup à une puissance maximale par des moyens simples en dépit des écarts inévitables de concentricité de la bague ou du collecteur sur lesquels frottent les balais en applique, les balais (6; 7; 8) sont montés pivotant sur un axe qui s'étend radialement à proximité de la surface et axialement sensiblement dans le sens de l'axe du collecteur (1) ou de la bague; dans un mode de réalisation, l'axe est constitué d'une goupille de guidage (31; 41) qui est maintenue dans une cage (2) entourant au moins partiellement le balai (6; 7) au voisinage de la surface du collecteur (1) et qui est introduite axialement dans une fente de guidage (61; 71) alignée avec le sens de pression des balais et ouverte sur la surface de la bague ou du collecteur (1), ou bien le balai (6) est serré tanguellement vers l'extérieur par le ressort de pression de balai (3a) et est monté en pivot sur des parties tangentielles de palier (33a; 34a).

IPC 1-7

H01R 39/40; H02K 13/10

IPC 8 full level

H01R 39/38 (2006.01); **H01R 39/40** (2006.01); **H02K 13/00** (2006.01); **H02K 13/10** (2006.01)

CPC (source: EP US)

H01R 39/381 (2013.01 - EP US); **H01R 39/40** (2013.01 - EP US)

Citation (search report)

See references of WO 9103857A1

Designated contracting state (EPC)

DE ES FR GB IT

DOCDB simple family (publication)

US 5329198 A 19940712; DE 59005292 D1 19940511; EP 0489866 A1 19920617; EP 0489866 B1 19940406; ES 2051024 T3 19940601;
JP H05500747 A 19930212

DOCDB simple family (application)

US 79341092 A 19920110; DE 59005292 T 19900823; EP 90914530 A 19900823; ES 90914530 T 19900823; JP 51355990 A 19900823