

Title (en)  
Lock for automobile safety belt.

Title (de)  
Schloss für Sicherheitsgurtsysteme in Fahrzeugen.

Title (fr)  
Fermeture pour ceinture de sécurité de véhicules automobiles.

Publication  
**EP 0489950 B1 19940720 (DE)**

Application  
**EP 90123817 A 19901211**

Priority  
EP 90123817 A 19901211

Abstract (en)  
[origin: EP0489950A1] The lock for safety belts in vehicles, which belts are provided with a tightening device which engages on said lock, is provided with a compensation mass (42) which prevents an inertia-conditioned movement of the release key (28) in the actuation direction at the end of the tightening stroke. The compensation mass is formed by a lever which is swivellably mounted on the housing and has a toothed element (44) which is in a permanent intermeshing engagement with a toothed rack (40) of the release key. Every time the release key is actuated, the lever (42) is swivelled, as a result of which its ease of movement is ensured even after the lock has been in use for a long time. <IMAGE>

IPC 1-7  
**A44B 11/25**

IPC 8 full level  
**A44B 11/25** (2006.01)

CPC (source: EP US)  
**A44B 11/2523** (2013.01 - EP US); **Y10T 24/45623** (2015.01 - EP US); **Y10T 24/45634** (2015.01 - EP US); **Y10T 24/45644** (2015.01 - EP US)

Citation (examination)  
EP 0369354 A2 19900523 - SISPA SICHERUNGS SPANGENVERSCH [DE]

Cited by  
DE4401291C1; CN108327164A; EP0868860A1; US6088890A

Designated contracting state (EPC)  
DE ES FR GB IT SE

DOCDB simple family (publication)  
**EP 0489950 A1 19920617; EP 0489950 B1 19940720**; DE 59006528 D1 19940825; ES 2032370 T1 19930216; ES 2032370 T3 19941216;  
JP H04276206 A 19921001; JP H0642845 B2 19940608; US 5115543 A 19920526

DOCDB simple family (application)  
**EP 90123817 A 19901211**; DE 59006528 T 19901211; ES 90123817 T 19901211; JP 32057491 A 19911204; US 79316691 A 19911118