

Title (en)

Device for cutting tiles and/or plates, for example roofing tiles.

Title (de)

Einrichtung zum Schneiden von Fliesen und/oder Platten beispielsweise Dachziegel.

Title (fr)

Dispositif pour couper des carreaux ou des plaques par exemple tuile.

Publication

EP 0490268 A1 19920617 (DE)

Application

EP 91120885 A 19911205

Priority

AT 254790 A 19901214

Abstract (en)

The device serves to cut tiles and/or plates and has an elongated support part for the workpieces, on the narrow sides of which bearing blocks are arranged. The latter carry guide rails running parallel to the longitudinal extent of the support part and arranged above the same. A slide can be displaced along these guide rails. Mounted on this slide is an actuating lever (6) which carries the cutting tool (9), has an actuating handle and can be pivoted about a pivot axis (28). The actuating lever (6) is mounted so as to be vertically adjustable inside the slide. An adjusting lever (19) pivotable about the axis (28) stationary in the slide is provided in or parallel to the pivoting plane of the actuating lever (6). Its free end directed towards the actuating handle of the actuating lever (6) can be secured to the latter. A bearing journal (31) lying parallel to the pivot axis (28) of the adjusting lever (19) is linked to the latter. The bearing journal (31) for the actuating lever (6) lies nearer to the pivot axis (28) of the adjusting lever (19) than to its free end. The adjusting lever (19) is of one-armed design and carries at its end a clamping screw (30) which passes through a circular-arc-shaped recess (24) on the actuating lever (6). <IMAGE>

Abstract (de)

Die Einrichtung dient zum Schneiden von Fliesen und/oder Platten und hat einen länglichen Auflageteil für die Werkstücke, an dessen Schmalseiten Lagerböcke angeordnet sind. Diese tragen parallel zur Längserstreckung des Auflageteiles verlaufende und oberhalb desselben angeordnete Führungsschienen. Entlang dieser Führungsschienen ist ein Schlitten verschiebbar. An diesem ist ein das Schneidwerkzeug (9) tragender, einen Betätigungsgriff aufweisender, um eine Schwenkachse (28) schwenkbarer Betätigungshebel (6) gelagert. Der Betätigungshebel (6) ist innerhalb des Schlittens höhenverstellbar gelagert. In oder parallel zur Schwenkebene des Betätigungshebels (6) ist ein um die im Schlitten ortsfeste Achse (28) schwenkbarer Stellhebel (19) vorgesehen. Dessen gegen den Betätigungsgriff des Betätigungshebels (6) gerichtete freie Ende ist an diesem festlegbar. Am Stellhebel (19) ist ein zu seiner Schwenkachse (28) parallel liegender Lagerzapfen (31) angelenkt. Der Lagerzapfen (31) für den Betätigungshebel (6) liegt näher der Schwenkachse (28) des Stellhebels (19) als dessen freiem Ende. Der Stellhebel (19) ist einarmig ausgebildet und trägt an seinem Ende eine Klemmschraube (30), die eine kreisbogenförmige Aussparung (24) am Betätigungshebel (6) durchsetzt. <IMAGE>

IPC 1-7

B28D 1/22

IPC 8 full level

B28D 1/22 (2006.01)

CPC (source: EP)

B28D 1/225 (2013.01)

Citation (search report)

- [A] EP 0387142 A1 19900912 - TOMECHANIC SA [FR]
- [A] US 4693232 A 19870915 - YASUGA MASAKI [JP]
- [A] EP 0277827 A1 19880810 - PLAS PLUGS LTD [GB]
- [A] JP S57177709 U 19821110
- [A] US 3399586 A 19680903 - INSOLIO THOMAS A, et al
- [A] US 4175684 A 19791127 - BUTLER JAMES K [US]
- [A] DE 318466 C
- [A] CH 384787 A 19650226 - COURVOISIER JEAN PIERRE [CH]

Cited by

ES2142736A1; AT15477U1; US5480081A; CN106592393A; EP2218564A1; ITMI20090186A1; WO2021119777A1

Designated contracting state (EPC)

AT CH DE ES FR IT LI

DOCDB simple family (publication)

EP 0490268 A1 19920617; EP 0490268 B1 19960306; AT 399120 B 19950327; AT A254790 A 19940815; AT E134924 T1 19960315; DE 59107512 D1 19960411

DOCDB simple family (application)

EP 91120885 A 19911205; AT 254790 A 19901214; AT 91120885 T 19911205; DE 59107512 T 19911205