

Title (en)

Device for cooling the pressing tools of a pressing machine and methods for its operation.

Title (de)

Einrichtung zum Kühlen der Presswerkzeuge einer Stauchpresse und Verfahren zum Betreiben der Einrichtung.

Title (fr)

Dispositif de refroidissement des outils de matriçage d'une presse à refouler et procédé pour son fonctionnement.

Publication

EP 0492227 B1 19941109 (DE)

Application

EP 91121014 A 19911207

Priority

DE 4041787 A 19901224

Abstract (en)

[origin: EP0492227A1] The invention relates to a device for cooling the pressing tools (9) of a pressing machine (1) for reducing the width of rolled stock, in particular the width of slabs (10) in hot wide-strip roughing trains with tool carriers (8) which are arranged on both sides at the edge of the slab, hold mutually facing pressing tools (9) and can be moved relative to one another. It is proposed that the pressing machine (1) should have at least one coolant nozzle (18) directed at the regions of the front edge (17) of each pressing tool (9), the device preferably being operated in such a way that the region of the front edge (17) of each pressing tool (9) is cooled continuously by a spray of coolant. <IMAGE>

IPC 1-7

B21B 15/00; B21J 1/04

IPC 8 full level

B21K 29/00 (2006.01); **B21B 15/00** (2006.01); **B21J 1/04** (2006.01)

CPC (source: EP KR US)

B21B 15/00 (2013.01 - KR); **B21B 15/005** (2013.01 - EP US); **B21J 1/04** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE DE ES FR GB GR IT NL SE

DOCDB simple family (publication)

EP 0492227 A1 19920701; EP 0492227 B1 19941109; AT E113874 T1 19941115; CN 1034558 C 19970416; CN 1062859 A 19920722; DE 4041787 A1 19920625; DE 59103501 D1 19941215; ID 813 B 19960717; KR 100197640 B1 19990615; KR 920011597 A 19920724; RU 2018407 C1 19940830; TW 206169 B 19930521; US 5349842 A 19940927

DOCDB simple family (application)

EP 91121014 A 19911207; AT 91121014 T 19911207; CN 91111842 A 19911224; DE 4041787 A 19901224; DE 59103501 T 19911207; ID 911174 A 19911218; KR 910022569 A 19911210; SU 5010421 A 19911223; TW 80109207 A 19911123; US 81210491 A 19911223