

Title (en)
Yarn detector.

Title (de)
Fadenwächter.

Title (fr)
DéTECTeur de fil.

Publication
EP 0495229 B1 19951102 (DE)

Application
EP 91121911 A 19911220

Priority
CH 5291 A 19910110

Abstract (en)
[origin: EP0495229A1] The yarn detector serves for detecting the passage of a yarn (F) moved in the transverse direction and contains a pivoting member (B) actuatable by the yarn and a sensor (7) monitoring the actuation of this pivoting member. The pivoting member (B) is designed so that, during the passage of a yarn, a deflection out of its position of rest and thereafter a return to this take place, the sensor (7) being designed to detect this return. The pivoting member (B) is elastic and in one piece and the sensor (7) is pressure-sensitive. The sector of use is yarn stores and yarn-transfer devices, especially those in weaving and in warp preparation. <IMAGE>

IPC 1-7
B65H 63/032; D03J 1/14

IPC 8 full level
B65H 63/00 (2006.01); **B65H 63/032** (2006.01); **D03D 51/18** (2006.01); **D03J 1/14** (2006.01)

CPC (source: EP KR US)
B65H 63/0327 (2013.01 - EP US); **D03J 1/14** (2013.01 - KR); **B65H 2701/31** (2013.01 - EP US)

Designated contracting state (EPC)
AT BE DE DK ES FR GB IT LU NL SE

DOCDB simple family (publication)
EP 0495229 A1 19920722; EP 0495229 B1 19951102; AT E129688 T1 19951115; AU 8970591 A 19920716; CA 2056686 A1 19920711; CH 682676 A5 19931029; CS 5892 A3 19920812; CZ 281497 B6 19961016; DE 59106824 D1 19951207; DK 0495229 T3 19951218; ES 2080881 T3 19960216; JP H04300349 A 19921023; KR 920014969 A 19920826; PT 99994 A 19940331; PT 99994 B 19990226; RU 2046857 C1 19951027; TR 27356 A 19950117; US 5428878 A 19950704

DOCDB simple family (application)
EP 91121911 A 19911220; AT 91121911 T 19911220; AU 8970591 A 19911213; CA 2056686 A 19911129; CH 5291 A 19910110; CS 5892 A 19920109; DE 59106824 T 19911220; DK 91121911 T 19911220; ES 91121911 T 19911220; JP 36100491 A 19911218; KR 920000041 A 19920106; PT 9999492 A 19920108; SU 5010663 A 19920109; TR 992 A 19920106; US 22912294 A 19940418