

Title (en)
Dartboard

Title (de)
Wurfpfeil-Scheibe

Title (fr)
Cible de jeu de fléchettes

Publication
EP 0495539 B1 19960207 (DE)

Application
EP 92106564 A 19890517

Priority

- DE 3834625 A 19881011
- DE 3826898 A 19880808
- EP 89108870 A 19890517

Abstract (en)

[origin: EP0354305A2] A dartboard consists of a frame (2) which within itself limits a plurality of zones, in each of which a spring-loaded segment (14, 24) is guided so as to be axially displaceable. So that a reliable hit indication is guaranteed even when the dart hits off-centre, pins (12, 22) are mounted in the frame (2) so as to be axially displaceable and bear with their front side on the rear side of the segments (14, 24), the pins (12, 22) being so spring-loaded (12', 44) that they endeavour to move the segments (14, 24) forwards (Figure 4). <IMAGE>
[origin: EP0354305A2] The dartboard comprises a frame (2) forming a number of sections, in each of which a spring-loaded segment (14) slides in the axial direction. Pins (12, 22), sliding axially in the frame, bear via their forward ends against the rear faces of the segments. They are spring-loaded to thrust the segments forwards. Lugs (15) are pref. provided on the segments, limiting their forward movement.

IPC 1-7
F41J 3/00

IPC 8 full level
F41J 3/00 (2006.01); **F41J 5/052** (2006.01)

CPC (source: EP)
F41J 3/0066 (2013.01); **F41J 5/052** (2013.01)

Cited by
US6116607A; US5669609A; US6089571A; DE102008044077A1; GB2273665A; US5417437A; WO9831980A1

Designated contracting state (EPC)
AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)
EP 0354305 A2 19900214; EP 0354305 A3 19900919; EP 0354305 B1 19930505; AT E134034 T1 19960215; DE 3834625 A1 19900215; DE 3834625 C2 19900809; DE 58904256 D1 19930609; DE 58909603 D1 19960321; DE 8915963 U1 19921001; EP 0495539 A2 19920722; EP 0495539 A3 19920930; EP 0495539 B1 19960207; ES 2039748 T3 19931001

DOCDB simple family (application)
EP 89108870 A 19890517; AT 92106564 T 19890517; DE 3834625 A 19881011; DE 58904256 T 19890517; DE 58909603 T 19890517; DE 8915963 U 19890517; EP 92106564 A 19890517; ES 89108870 T 19890517