

Title (en)

CHARGING DEVICE DISPOSED CLOSE TO MEMBER TO BE CHARGED AND IMAGE FORMING APPARATUS USING SAME

Publication

EP 0496399 A3 19930707 (EN)

Application

EP 92101088 A 19920123

Priority

- JP 665191 A 19910124
- JP 1100391 A 19910131

Abstract (en)

[origin: EP0496399A2] A charging device includes a charging member opposed to a member to be charged with a smaller clearance therebetween; voltage application means for applying an oscillating voltage between the member to be charged and said charging member; wherein said charging member is provided with a resistance layer, and a reactance of the resistance layer against the oscillating voltage is smaller than a resistance of the resistance layer. <IMAGE>

IPC 1-7

G03G 15/02

IPC 8 full level

G03G 15/02 (2006.01)

CPC (source: EP KR)

G03G 15/02 (2013.01 - KR); **G03G 15/0208** (2013.01 - EP); **G03G 15/025** (2013.01 - EP)

Citation (search report)

- [X] EP 0308185 A2 19890322 - CANON KK [JP]
- [A] US 4727453 A 19880223 - EWING JOAN R [US]
- [A] EP 0338546 A2 19891025 - CANON KK [JP]
- [XP] EP 0431559 A2 19910612 - CANON KK [JP]
- [A] PATENT ABSTRACTS OF JAPAN vol. 10, no. 64 (P-436)(2121) 14 March 1986 & JP-A-60 205 550 (FUJI XEROX K.K.) 17 October 1985
- [A] PATENT ABSTRACTS OF JAPAN vol. 13, no. 460 (P-946)18 October 1989 & JP-A-01 179 957 (CANON INC) 18 July 1989

Cited by

EP1093030A1; EP1074893A1; US5863695A; EP0831377A3; US6405006B1; US6360065B1; US7962068B2; US7664434B2; WO2006025597A1; WO2006070904A1

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

EP 0496399 A2 19920729; EP 0496399 A3 19930707; KR 920015171 A 19920826

DOCDB simple family (application)

EP 92101088 A 19920123; KR 920001005 A 19920124