

Title (en)
HANGING SCAFFOLD.

Title (de)
HÄNGENDES GERÜST.

Title (fr)
ECHAFAUDAGE SUSPENDU.

Publication
EP 0497861 B1 19950111 (EN)

Application
EP 90916394 A 19901026

Priority

- SE 9000693 W 19901026
- SE 9002890 A 19900911
- SE 8903607 A 19891027

Abstract (en)
[origin: WO9106729A1] A hanging scaffold for use on buildings includes at least two attachment devices (18-20) which are permanently attached in the roof projection region of the building. Each of the attachment devices is intended to detachably secure a framework (16, 26, 27) which, in turn, support the floor structure and the balustrade (15) of the scaffold. Each attachment device (18-20) has the form of a substantially U-shaped bracket (18, 19) which is intended to straddle a rafter or ceiling joist forming a truss part (10) of the building, and a bolt (20) which extends horizontally through this truss part (10) and through the bracket legs (18) located on opposite sides of the truss part. The upper end of an elongated profiled member (16) forming part of the framework can be hung from the bolt (20).

IPC 1-7
E04G 3/10; E04G 3/12

IPC 8 full level
E04G 3/22 (2006.01); **E04G 3/26** (2006.01)

IPC 8 main group level
E04G (2006.01)

CPC (source: EP)
E04G 3/22 (2013.01); **E04G 3/26** (2013.01); **E04G 5/041** (2013.01)

Cited by
EP3957807A1; EP4293175A3

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB IT LI NL SE

DOCDB simple family (publication)
WO 9106729 A1 19910516; AT E117039 T1 19950115; AU 7040391 A 19910531; DE 69016041 D1 19950223; DE 69016041 T2 19950524;
DK 0497861 T3 19950320; EP 0497861 A1 19920812; EP 0497861 B1 19950111; FI 921883 A0 19920427; FI 921883 A 19920427;
NO 177112 B 19950410; NO 177112 C 19950719; NO 921599 D0 19920424; NO 921599 L 19920424

DOCDB simple family (application)
SE 9000693 W 19901026; AT 90916394 T 19901026; AU 7040391 A 19901026; DE 69016041 T 19901026; DK 90916394 T 19901026;
EP 90916394 A 19901026; FI 921883 A 19920427; NO 921599 A 19920424