

Title (en)  
Capped electric lamp.

Title (de)  
Gesockelte elektrische Lampe.

Title (fr)  
Lampe électrique à culot.

Publication  
**EP 0499316 A1 19920819 (EN)**

Application  
**EP 92200323 A 19920206**

Priority  
NL 9100265 A 19910215

Abstract (en)  
The lamp comprises a lamp cap (10) with a metal shell (30) in which an insulator body (50), with a circumferential outer surface (51) between a first, and a second end face (52, 53 respectively) is locked. The insulator body (50) has recesses (54a, 54c) in its second end face (53) that extend from a boundary surface (55a, 55c), which is transverse to the second end face (53), up to the circumferential outer surface (51). The metal shell (30) has, at a cross-section (X-X), first tongues (31a, 31c) which are present in the recesses (54a, 54c). The first tongues (31a, 31c) point obliquely away from the first end face (52) and press with their free ends (32a, 32c) against the boundary surfaces (55a, 55c) of the recesses (54a, 54c). <IMAGE>

IPC 1-7  
**H01J 5/50**; **H01K 1/46**

IPC 8 full level  
**H01J 5/50** (2006.01); **H01K 1/46** (2006.01)

CPC (source: EP)  
**H01J 5/50** (2013.01); **H01K 1/46** (2013.01)

Citation (search report)  
[AD] DE 8907108 U1 19890810

Cited by  
WO0171771A1; WO9850943A1; WO0171772A1

Designated contracting state (EPC)  
BE DE FR GB IT NL

DOCDB simple family (publication)  
**EP 0499316 A1 19920819**; HU 207905 B 19930628; HU 9200419 D0 19920428; HU T60568 A 19920928; JP H0562654 A 19930312

DOCDB simple family (application)  
**EP 92200323 A 19920206**; HU 9200419 A 19920212; JP 2823892 A 19920214