

Title (en)

Releasable assembly device of a stay with a link arm.

Title (de)

Vorrichtung zum lösbaren Verbinden eines Ausstellarms mit einem Hilfslenker.

Title (fr)

Dispositif pour l'assemblage décrochable d'un bras de compas avec un bras auxiliaire.

Publication

EP 0499708 B1 19950809 (DE)

Application

EP 91121205 A 19911211

Priority

DE 9102070 U 19910222

Abstract (en)

[origin: EP0499708A1] So that the articulated connection between a swivel arm (9) and an auxiliary link (12) can be made easily, but also released easily, the bearing bolt (10) on the swivel arm (9) is equipped with a circumferential groove (14), and its free end is chamfered (15). Moreover, two blocking jaws (17, 18) are held pivotably and/or bendably on the auxiliary link (12) and project with inner regions (20) and (21) into the range of movement of the bearing bolt (10). When the bearing bolt (10) is being inserted into the bearing bore (11), the two blocking jaws (17, 18) shift sideways in opposite directions. As soon as the circumferential groove (14) has come into the pivoting range of the blocking jaws (17, 18), these can spring back and enter the groove with a blocking effect. A manual release of this blocking device is possible if the free blocking-jaw ends are connected to, especially made in one piece with, a shackle-like actuating member (33) which can be pressed down resiliently. <IMAGE>

IPC 1-7

E05D 15/52; **E05C 17/24**; **F16B 21/18**

IPC 8 full level

E05C 17/24 (2006.01); **E05D 15/52** (2006.01); **F16B 21/18** (2006.01)

CPC (source: EP)

E05C 17/24 (2013.01); **E05D 15/5205** (2013.01); **E05Y 2600/53** (2013.01); **E05Y 2900/148** (2013.01)

Cited by

EP1612354A3; GB2391585A; GB2421267A; GB2287748A; GB2287748B; CN117428445A; EP1612354A2; WO2014013308A1

Designated contracting state (EPC)

AT BE DE FR GB IT NL

DOCDB simple family (publication)

EP 0499708 A1 19920826; **EP 0499708 B1 19950809**; AT E126317 T1 19950815; DE 59106226 D1 19950914; DE 9102070 U1 19910516

DOCDB simple family (application)

EP 91121205 A 19911211; AT 91121205 T 19911211; DE 59106226 T 19911211; DE 9102070 U 19910222