

Title (en)
Safety closures.

Title (de)
Sicherheitsverschluss.

Title (fr)
Fermeture de sécurité.

Publication
EP 0500265 B1 19950517 (EN)

Application
EP 92301197 A 19920213

Priority
GB 9103330 A 19910216

Abstract (en)
[origin: EP0500265A1] With reference to Figures 3 to 8, a closure for a container is moulded from a suitable plastics material and comprises a cap with a top wall 1 and skirt 2. The lower edge of the skirt 2 is joined by a breakable web 3 to a tear-off band 4, and the band 4 is joined in turn by a similar web 5 to a captive band 6. The interior of the skirt 2 is formed with an interrupted bead defined by two internal circumferentially spaced shoulders 7 (Figure 3) with a gap 8 between them, a vestigial bead 9 and a substantial inwardly projecting lug 10. On the outside of the cap in alignment with the lug 10 is a finger tab 11 (Figure 4) to facilitate removal of the cap when it has first been turned to the right angular position on the neck of the associated container, with the lug 10 in a gap 12 in the bead 13 (Figures 7 and 8) on the neck of the container. <IMAGE> <IMAGE>

IPC 1-7
B65D 55/02

IPC 8 full level
B65D 50/06 (2006.01)

CPC (source: EP)
B65D 50/061 (2013.01)

Cited by
WO9501920A1; WO2007068038A1

Designated contracting state (EPC)
BE DE ES FR GB GR IT PT

DOCDB simple family (publication)
EP 0500265 A1 19920826; EP 0500265 B1 19950517; DE 69202489 D1 19950622; DE 69202489 T2 19951109; ES 2072702 T3 19950716;
GB 2253391 A 19920909; GB 9103330 D0 19910403; IE 68601 B1 19960626; IE 920488 A1 19920826

DOCDB simple family (application)
EP 92301197 A 19920213; DE 69202489 T 19920213; ES 92301197 T 19920213; GB 9103330 A 19910216; IE 920488 A 19920214