

Title (en)  
ELECTRICAL CONNECTOR.

Title (de)  
LEITUNGSSTECKER.

Title (fr)  
FICHE ELECTRIQUE.

Publication  
**EP 0500526 B1 19940112 (DE)**

Application  
**EP 90906125 A 19900426**

Priority  
DE 8912596 U 19891024

Abstract (en)  
[origin: WO9106989A1] The electrical connector of the invention has contact elements located in adjacent chambers in an insulating housing (1), each element having a crimping zone permitting bunched conductors to be connected. In addition, for each chamber in the housing, there is a slot (16) designed to hold a locking strip (31) which acts on one edge (22) of the respective contact element to produce a locking effect. In order to avoid the spread conductor ends from straying into neighbouring chambers and causing a short circuit when the locking strip (31) is inserted across the longitudinal axis of the contact elements, each crimping zone is located on that side of the wall of the part-tubular contact element (2) which is remote from the locking edge.

IPC 1-7  
**H01R 13/436**

IPC 8 full level  
**H01R 13/11** (2006.01); **H01R 13/436** (2006.01)

CPC (source: EP US)  
**H01R 13/11** (2013.01 - EP US); **H01R 13/4361** (2013.01 - EP US)

Designated contracting state (EPC)  
BE DE ES FR GB IT

DOCDB simple family (publication)  
**DE 8912596 U1 19910228**; DE 59004259 D1 19940224; EP 0500526 A1 19920902; EP 0500526 B1 19940112; ES 2047925 T3 19940301;  
PT 8510 T 19921130; PT 8510 U 19950912; PT 95653 A 19920731; US 5252095 A 19931012; WO 9106989 A1 19910516

DOCDB simple family (application)  
**DE 8912596 U 19891024**; DE 59004259 T 19900426; DE 9000306 W 19900426; EP 90906125 A 19900426; ES 90906125 T 19900426;  
PT 851092 U 19920526; PT 9565390 A 19901023; US 83876092 A 19920317