

Title (en)  
ELECTROMAGNETIC RELAY

Publication  
**EP 0502842 B1 19931013 (DE)**

Application  
**EP 89912405 A 19891116**

Priority  
DE 8900722 W 19891116

Abstract (en)  
[origin: WO9107770A1] In the relay described, the magnet system is fixed in the upper zone of a lid-like housing, and the contact system (8) is inserted into the housing, through the open underside of the housing, far enough for the contact (91, 92) to close when the magnet system is in the excited state. Following further insertion by a given excess distance, the edge (82a) of the contact system (8) is connected to the housing (1) without a stop. This enables manufacturing variations to be compensated for during assembly, obviating the need for subsequent adjustment of the contact system.

IPC 1-7  
**H01H 49/00**; **H01H 50/04**

IPC 8 full level  
**H01H 49/00** (2006.01); **H01H 50/04** (2006.01); **H01H 50/64** (2006.01)

CPC (source: EP)  
**H01H 49/00** (2013.01); **H01H 50/04** (2013.01)

Citation (examination)  
FR 235469 A

Designated contracting state (EPC)  
AT BE CH DE ES FR GB IT LI

DOCDB simple family (publication)  
**WO 9107770 A1 19910530**; AT E95947 T1 19931015; DE 58905927 D1 19931118; EP 0502842 A1 19920916; EP 0502842 B1 19931013; JP 3217345 B2 20011009; JP H05501629 A 19930325

DOCDB simple family (application)  
**DE 8900722 W 19891116**; AT 89912405 T 19891116; DE 58905927 T 19891116; EP 89912405 A 19891116; JP 51155289 A 19891116