

Title (en)
PRESSURE SWITCH

Publication
EP 0507002 A3 19921209 (DE)

Application
EP 91119839 A 19911121

Priority
CH 97591 A 19910402

Abstract (en)
[origin: EP0507002A2] The switching device (26) of the pressure switch (10) has a stationary contact element (30) and a moving contact element (32) which is coupled to a snap spring (50). These contact elements (30, 32), which form a switch contact, are arranged between a clamping-in point (62) on the housing and an operating point (44) at which a membrane (24) engages by means of a plunger (46) on a leaf spring (34) which operates the switch contact. In this case, the operating point (44) is located on a longer lever arm than the switch contact. This causes a force transfer from the membrane movement to the switch contact and, through the amplification of the contact pressure, ensures increased electrical switching reliability. <IMAGE>

IPC 1-7
H01H 35/34; H01H 35/26; H01H 5/18; H01H 35/02; H01H 11/00

IPC 8 full level
H01H 35/26 (2006.01); **H01H 35/34** (2006.01); **H01H 5/18** (2006.01)

CPC (source: EP KR)
H01H 35/24 (2013.01 - KR); **H01H 35/2607** (2013.01 - EP); **H01H 35/34** (2013.01 - EP); **H01H 5/18** (2013.01 - EP)

Citation (search report)

- US 4990728 A 19910205 - JOYCE RONALD S [US]
- US 2554266 A 19510522 - PAULY JACOB L
- EP 0155390 A2 19850925 - MIRACO INC [US]
- US 2800549 A 19570723 - GUTHRIE GEORGE G
- US 3436502 A 19690401 - EGLI ERNST M
- US 4410776 A 19831018 - STOLL DONALD H [US]
- FR 2089534 A5 19720107 - GRUNER KG RELAIS FABRIK
- DE 6920608 U 19701022 - BORGGMANN KG W [DE]
- US 3830995 A 19740820 - CARLSTEDT S
- DE 3826749 C1 19891102
- US 4272660 A 19810609 - MAYER WILLIAM R, et al
- GB 1433391 A 19760428 - DIAMON H CONTROLS LTD

Cited by
EP1858040A4; EP0595210A1; US5421242A

Designated contracting state (EPC)
CH DE FR GB IT LI NL

DOCDB simple family (publication)
EP 0507002 A2 19921007; EP 0507002 A3 19921209; KR 930011035 A 19930623

DOCDB simple family (application)
EP 91119839 A 19911121; KR 920004850 A 19920325