

Title (en)  
Gas discharge switch.

Title (de)  
Gasentladungsschalter.

Title (fr)  
Interrupteur à décharge dans un gaz.

Publication  
**EP 0510232 B1 19951018 (DE)**

Application  
**EP 91106732 A 19910425**

Priority  
EP 91106732 A 19910425

Abstract (en)  
[origin: EP0510232A1] The gas-discharge switch for a low-pressure gas discharge contains at least two main electrodes. The distance d between the main electrodes and the pressure p of an operating gas are selected such that the starting voltage reduces as the product p x d increases. According to the invention, a hollow electrode (10) which is connected to a triggering-voltage source (17) is allocated to the discharge path (8). This hollow electrode (10) is connected to the anode (3) via an anode resistor RA. The hollow electrode (10) can preferably also be connected to the cathode (2), via a resistor RK. This design of the starting device results in pre-ionisation within the hollow electrode (10), and corresponding simplification of the starting device. <IMAGE>

IPC 1-7  
**H01T 2/02; H01J 17/44**

IPC 8 full level  
**H01J 17/44** (2006.01); **H01T 2/02** (2006.01)

CPC (source: EP US)  
**H01T 2/02** (2013.01 - EP US)

Citation (examination)  
JAPANESE JOURNAL OF APPLIED PHYSICS Bd. 29, Nr. 212 Februar 1990 , TOKYO, JP Seiten 371 - 374; A. TINSCHMANN ET AL.: 'The Pseudospark Switch A High-Voltage Gas Discharge Switch for High-Power Applications'

Designated contracting state (EPC)  
CH DE FR GB IT LI

DOCDB simple family (publication)  
**EP 0510232 A1 19921028; EP 0510232 B1 19951018**; DE 59106733 D1 19951123; JP 3153623 B2 20010409; JP H05198263 A 19930806;  
US 5189345 A 19930223

DOCDB simple family (application)  
**EP 91106732 A 19910425**; DE 59106733 T 19910425; JP 13012192 A 19920422; US 87199292 A 19920422