

Title (en)
Skiboot.

Title (de)
Skischuh.

Title (fr)
Chaussure de ski.

Publication
EP 0514762 A2 19921125 (DE)

Application
EP 92108117 A 19920514

Priority
CH 155191 A 19910523

Abstract (en)
The ski boot has a lower shell (1) and a front shaft part (2) and a rear shaft part (3) which consists of a lower section (4) articulated pivotably on the lower shell (1) and of an upper section (5) articulated pivotably on the lower section by means of a pivot pin (17). The closure means have a tensioning cable (18) fastened with the end on the front shaft part (2) and a tensioning lever (20) which is connected to the other tensioning cable end and the lever pin (21) of which is arranged on a spring mounting (22) situated on the rear side of the rear shaft part (3). This mounting is secured by means of a locking catch (23) on a locking pin (25) which is rigidly connected to the lower section (4) of the rear shaft part. A pressure spring (24) arranged in the spring mounting is tensioned when the tensioning lever (20) is pivoted downwards. The ski boot is to reduce the risk of injury in backward lean, in particular in the knee region. In backward lean, the upper section (5) of the rear shaft part (3) is first pivoted backwards and the locking catch (23) passes out of its locking position. Subsequently, by movement of the spring mounting, the system consisting of tensioning lever (20) and spring mounting (22) passes backwards out of the upper dead centre position so that the lower section (4) of the rear shaft part can also pivot backwards into the open position. The leg is braked softly backwards in a two-stage opening movement. <IMAGE>

Abstract (de)
Der Skischuh weist eine Unterschale (1) sowie einen vorderen Schaftteil (2) und einen rückwärtigen Schaftteil (3) auf, der aus einem an der Unterschale (1) schwenkbar angelenkten unteren Abschnitt (4) und einem an diesem mittels einer Schwenkachse (17) schwenkbar angelenkten oberen Abschnitt (5) besteht. Die Verschlussmittel weisen ein am vorderen Schaftteil (2) mit dem Ende befestigtes Spannkabel (18) und einen mit dem anderen Spannkabelende verbundenen Spannhebel (20) auf, dessen Hebelachse (21) an einer an der Rückseite des rückwärtigen Schaftteils (3) befindlichen Federhalterung (22) angeordnet ist. Diese ist mittels einer Rastklinke (23) an einer mit dem unteren Abschnitt (4) des rückwärtigen Schaftteils fest verbundenen Rastachse (25) festgehalten. Eine in der Federhalterung angeordnete Druckfeder (24) ist bei nach unten geschwenktem Spannhebel (20) gespannt. <IMAGE>

IPC 1-7
A43B 5/04; A43C 11/00; A43C 11/16

IPC 8 full level
A43B 5/04 (2006.01); **A43C 11/16** (2006.01)

CPC (source: EP)
A43B 5/0456 (2013.01); **A43C 11/16** (2013.01); **A43C 11/165** (2013.01)

Cited by
EP1110467A1; EP0968664A1; US11510454B2; US6263593B1; CH692232A5; US2015359292A1; US9743708B2; WO9722271A1; US6643955B2; WO2018165990A1; US6298584B1

Designated contracting state (EPC)
AT CH DE FR IT LI

DOCDB simple family (publication)
EP 0514762 A2 19921125; EP 0514762 A3 19930929; JP H05146301 A 19930615

DOCDB simple family (application)
EP 92108117 A 19920514; JP 13283092 A 19920525