

Title (en)
Electromagnetic trip device for a low current circuit breaker.

Title (de)
Elektromagnetischer Auslöser für einen Schwachstromschalter.

Title (fr)
Déclencheur électromagnétique pour un disjoncteur électrique à bas calibres.

Publication
EP 0515292 A1 19921125 (FR)

Application
EP 92420161 A 19920515

Priority
FR 9106309 A 19910521

Abstract (en)
The invention relates to an electromagnetic trip (24) for a low-current, in particular less than a few amperes, miniature circuit breaker. To avoid a magnetic leakage field around the trip, the yoke (60) includes a first ferromagnetic piece (62) serving as means of support to the coil (50) and cores (48,54) assembly, and a second ferromagnetic piece (64) assembled to the first of conjugate shape to form a complete screening member. Magnetic saturation of the electromagnetic is then retarded when a short-circuit current is detected. <IMAGE>

IPC 1-7
H01H 71/24

IPC 8 full level
H01H 71/24 (2006.01)

CPC (source: EP)
H01H 71/2454 (2013.01); H01H 71/2463 (2013.01)

Citation (search report)

- [XD] DE 2138381 A1 19730208 - SIEMENS AG
- [XD] FR 2592738 A1 19870710 - MERLIN GERIN [FR]
- [A] EP 0410257 A1 19910130 - SIEMENS AG [DE]
- [A] EP 0008558 A1 19800305 - LEGRAND SA [FR]
- [A] EP 0236576 A1 19870916 - MATSUSHITA ELECTRIC WORKS LTD [JP]

Cited by
FR2779567A1; EP1906427A1; EP0834895A1; FR2753836A1; US5894257A; EP1501112A1; FR2858106A1; CN1320580C; EP1583130A1; FR2868596A1; US6956454B1; WO9963564A1

Designated contracting state (EPC)
BE CH DE ES GB IT LI SE

DOCDB simple family (publication)
EP 0515292 A1 19921125; EP 0515292 B1 19950412; DE 69201999 D1 19950518; DE 69201999 T2 19951123; ES 2073896 T3 19950816; FR 2676860 A1 19921127; FR 2676860 B1 19940617

DOCDB simple family (application)
EP 92420161 A 19920515; DE 69201999 T 19920515; ES 92420161 T 19920515; FR 9106309 A 19910521