

Title (en)  
LOCKING CYLINDER AND KEY

Publication  
**EP 0516611 A3 19921209 (DE)**

Application  
**EP 92890103 A 19920429**

Priority  
AT 92091 A 19910502

Abstract (en)  
[origin: EP0516611A2] A locking cylinder (1) can be blocked by a key (15) having a mechanical code track with a height profiling at a plurality of height levels (27, 28, 29) identifiable on the lock side by a reading device which comprises an analog transmitter, for example a pressure-variable resistor, especially rubber resistor (19), in a measuring circuit (20). When the key (15) is inserted into a key channel (14), the code track is sensed by a tracer pin (13) and the code-dependent measurement quantity, for example the resistance values variable as a function of pressure, are detected in succession. They result in a code which is compared with the code of a code memory (22). If the codes agree, a release signal for an electromechanical locking device (26) is generated. Furthermore, the locking cylinder (1) can additionally have the conventional pin tumblers (4, 5, 6, 7, 8). <IMAGE>

IPC 1-7  
**E05B 49/00**

IPC 8 full level  
**E05B 49/00** (2006.01)

CPC (source: EP)  
**E05B 49/002** (2013.01)

Citation (search report)  
• [X] GB 2196685 A 19880505 - YALE SECURITY PROD LTD  
• [A] DE 3308487 A1 19831013 - GRUNDMANN GMBH GEB [AT]  
• [A] WO 8800635 A1 19880128 - LOWE & FLETCHER LTD [GB]  
• [A] WO 8800636 A1 19880128 - LOWE & FLETCHER LTD [GB]

Cited by  
CN106522686A; CN102003119A; DE102006012567A1; WO0060197A1

Designated contracting state (EPC)  
BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)  
**EP 0516611 A2 19921202; EP 0516611 A3 19921209; EP 0516611 B1 19960410**; AT 396282 B 19930726; AT A92091 A 19921115;  
DE 59205936 D1 19960515

DOCDB simple family (application)  
**EP 92890103 A 19920429**; AT 92091 A 19910502; DE 59205936 T 19920429