

Title (en)
SEALING ARRANGEMENT.

Title (de)
DICHTUNGSSANORDNUNG.

Title (fr)
DISPOSITIF D'ETANCHEITE.

Publication
EP 0517780 B1 19950125 (DE)

Application
EP 91905404 A 19910228

Priority

- DE 9100193 W 19910228
- DE 4006258 A 19900228

Abstract (en)
[origin: WO9113276A2] A sealing arrangement for sealing a gap (11) between two concentric, antagonistically mobile machine parts, the first machine part (3) having a smooth contact surface (5) and the second machine part (4) having a profiled section (6) facing the contact surface (5) of the first machine part (3), accommodates a packing ring (2). The profiled section (6) is bounded by a first flank (8) and a second flank (9). The packing ring has a curved peripheral surface (7) and a radial surface (13), either of which may be completely exposed to the high pressure side. A sealing edge (10) of the packing ring (2) is formed by the line of intersection of a conical surface (14) and the curved peripheral surface (7). The conical surface (14) merges into the radial surface (13). The packing ring of the invention has a defined pressing distribution and, if the curved peripheral surface (7) faces the high-pressure side, the whole surface of the packing ring is pressed non-positively against the second flank (9) by a pressurized medium.

IPC 1-7
F16J 15/32

IPC 8 full level
F16J 15/32 (2016.01)

CPC (source: EP)
F16J 15/32 (2013.01)

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)
WO 9113276 A2 19910905; WO 9113276 A3 19911114; AT E117780 T1 19950215; DE 59104427 D1 19950309; DK 0517780 T3 19950410;
EP 0517780 A1 19921216; EP 0517780 B1 19950125; ES 2074265 T3 19950901; JP H05503139 A 19930527; JP H0678788 B2 19941005

DOCDB simple family (application)
DE 9100193 W 19910228; AT 91905404 T 19910228; DE 59104427 T 19910228; DK 91905404 T 19910228; EP 91905404 A 19910228;
ES 91905404 T 19910228; JP 50527491 A 19910228