

Title (en)

Multipole electrical connector for electronic signal lines.

Title (de)

Mehrpoliger Steckverbinder für elektronische Signalleitungen.

Title (fr)

Connecteur électrique multipolaire pour lignes de signaux électroniques.

Publication

**EP 0517952 B1 19950614 (DE)**

Application

**EP 91119122 A 19911111**

Priority

DE 9107385 U 19910614

Abstract (en)

[origin: EP0517952A2] In the case of a multi-pole plug connector (1; 2; 3) having a housing (4) which is provided with at least one conductive shell (4.1), through which lines (12.1) carrying, in particular, digitised signals run and in which a planar filter (10), which is constructed on a base plate (11), is arranged, having capacitors which are provided for at least some of the signal lines (12.1) and are formed by a base electrode (14) which is fitted onto the base plate (11) and onto which a dielectric layer (15) and onto which in turn an opposing electrode (16) are fitted, in each case one of the electrodes (14; 16) being constructed continuously with the housing (4) as an earth electrode, and the other of the electrodes (16; 14) being divided into individual signal electrodes which are conductively connected to the signal lines (12.1), and the base plate (11) and dielectric layer (15) and at least one of the electrodes (14; 16) having cut-outs (12) for the signal lines (12.1) to pass through, in order to develop said plug connector such that, integrated into the multi-pole plug connector as a low-pass filter, said lines are able to withstand temperature differences without failures; in a continuation of the object it is intended to develop the multi-pole plug connectors to form filters which reliably filter out radio-frequency interference, it is proposed that the planar filter (10) have a capacitor for each of the pins of the signal lines (12.1), the base electrode (14), which is fitted onto the base plate (11) which is constructed from aluminium-oxidic or ferromagnetic ceramic, having further cut-outs (14.2) around the signal lines (12.1) in the region of the passages (12) for the signal lines (12.1), by means of which cut-outs (14.2) the dielectric layer (15) is anchored to the material of the base plate (11), connected via links (15.1) to said material of the base plate (11). <IMAGE>

IPC 1-7

**H01R 13/719**

IPC 8 full level

**H01R 13/719** (2011.01)

CPC (source: EP US)

**H01R 13/719** (2013.01 - EP US)

Cited by

DE19815488C1

Designated contracting state (EPC)

DE ES FR GB IT NL

DOCDB simple family (publication)

**DE 9107385 U1 19920716**; DE 59105732 D1 19950720; EP 0517952 A2 19921216; EP 0517952 A3 19930811; EP 0517952 B1 19950614; ES 2075305 T3 19951001; US 5242318 A 19930907

DOCDB simple family (application)

**DE 9107385 U 19910614**; DE 59105732 T 19911111; EP 91119122 A 19911111; ES 91119122 T 19911111; US 89847492 A 19920615