

Title (en)
Fluid pressure operated actuator

Title (de)
Druckmittelbetätigbarer Arbeitszylinder

Title (fr)
Vérin commandé par un fluide sous pression

Publication
EP 0519185 B2 19990811 (DE)

Application
EP 92107083 A 19920425

Priority
DE 4120170 A 19910619

Abstract (en)
[origin: EP0519185A1] The invention proposes a fluid pressure operated actuator (10) in which the directional control valve (13) controlling the actuator (10) is attached externally via a flange plate (12). As a casing, the actuator (10) has a cylinder barrel (11) designed as a special section tube, arranged in a uniformly distributed manner on the outer circumference of which are four profiled longitudinal struts (22 to 25) extending parallel to the longitudinal axis and to one another. The flange plate (12) is guided in axially displaceable and radially captive fashion on two (22, 23) of the longitudinal struts, these longitudinal struts (22, 23), which are hollow, forming ducts (36, 38) for the pressure fluid, via which the pressure-fluid connections lead to the pressure spaces (18, 21) on both sides of the piston (15). The actuator (10), which is of compact construction, requires few parts to carry the pressure fluid, thereby reducing the risk of the escape of leaking pressure fluid. <IMAGE>

IPC 1-7
F15B 15/20

IPC 8 full level
F15B 15/14 (2006.01); **F15B 15/20** (2006.01)

CPC (source: EP)
F15B 15/1428 (2013.01)

Cited by
GB2318616A; GB2318616B; DE10043647B4; FR2710372A1; US6170797B1; WO9508715A1; US11009048B1

Designated contracting state (EPC)
DE FR IT SE

DOCDB simple family (publication)
EP 0519185 A1 19921223; EP 0519185 B1 19941019; EP 0519185 B2 19990811; DE 4120170 A1 19921224; DE 59200647 D1 19941124

DOCDB simple family (application)
EP 92107083 A 19920425; DE 4120170 A 19910619; DE 59200647 T 19920425