

Title (en)

Lamp with an adjustable distance between the reflector and the lamp socket.

Title (de)

Leuchte mit zwischen Reflektor und Lampenfassung verstellbarem Abstand.

Title (fr)

Lampe à distance réglable entre le réflecteur et la douille d'ampoule.

Publication

**EP 0521267 B1 19950927 (DE)**

Application

**EP 92107925 A 19920512**

Priority

DE 4121576 A 19910629

Abstract (en)

[origin: EP0521267A2] Luminar having a housing (12) which accommodates a reflector (30) and a lamp holder (40) arranged in an extension of the reflector axis behind an opening (46) in the reflector, characterised in that the reflector is arranged in an adjusting ring (18) that is arranged rotatably in the housing and projects from the housing opening with a handling part (20), and in that the lamp holder is arranged on a holder carrier (36), which is retained rotationally locked in the housing and can be adjusted in the direction of the reflector axis with the aid of the adjusting ring via a thread or a thread-like control surface (48). <IMAGE>

IPC 1-7

**F21V 19/02**

IPC 8 full level

**F21V 19/02** (2006.01)

CPC (source: EP)

**F21V 19/02** (2013.01)

Cited by

EP0563889A3; DE102005007348A1; GB2321301A; US6045236A; WO2006087126A1; WO9712176A1

Designated contracting state (EPC)

AT CH DE DK ES FR GB IT LI NL SE

DOCDB simple family (publication)

**EP 0521267 A2 19930107; EP 0521267 A3 19930428; EP 0521267 B1 19950927**; AT E128536 T1 19951015; DE 4121576 A1 19930107; DE 4121576 C2 19940317; DE 59203800 D1 19951102

DOCDB simple family (application)

**EP 92107925 A 19920512**; AT 92107925 T 19920512; DE 4121576 A 19910629; DE 59203800 T 19920512