

Publication

EP 0521419 A3 19950111

Application

EP 92110911 A 19920627

Priority

GB 9114354 A 19910703

Abstract (en)

[origin: EP0521419A2] A television receiver has a switched mode power supply (TP29, LP36) for regulating output voltages including the B+ output to a flyback transformer (FBT), by generation of output pulses to a power transformer (LP36). A controller (20) for the power supply is coupled in two feedback loops, one responsive to a pulse width modulator (92) coupled to the flyback transformer and the other comparing the output voltage with an internal reference (in 34) for free running operation. The first feedback loop takes precedence and is active in the run mode of the television receiver. In the standby mode when horizontal rate pulses are absent, the second feedback loop takes over. The second feedback loop has a different reference level than the first, such that when switching from the run mode to the standby mode a transition interval occurs in which no pulses are output by the controller, thereby causing the B+ voltage to the flyback transformer to fall. During this transition interval, horizontal scanning signals continue at falling amplitude, and a signal is input to the kinescope drivers (84), thereby collapsing the picture and draining the ultor voltage on the screen anode (Csc). The reoccurrence of controller pulses when the output voltage of the power transformer (LP36) has fallen to the new lower reference level is used to positively switch operation of the receiver at the conclusion of the transition interval. <IMAGE> <IMAGE> <IMAGE> <IMAGE> <IMAGE> <IMAGE>

IPC 1-7

H04N 3/185

IPC 8 full level

H04N 3/185 (2006.01); **H04N 5/63** (2006.01)

CPC (source: EP KR US)

H04N 3/185 (2013.01 - EP US); **H04N 5/63** (2013.01 - EP KR US); **H02M 1/0032** (2021.05 - EP US); **Y02B 70/10** (2013.01 - EP US)

Citation (search report)

- [A] DE 4025457 A1 19910214 - THOMSON CONSUMER ELECTRONICS [US]
- [DXA] "TEA2260 High Performance Driver Circuit for SMPS", APPLICATION NOTES OF SGS-THOMSON MICROELECTRONICS, April 1989 (1989-04-01), GRENOBLE, pages 1 - 34
- [XA] MAIGE: "A universal power supply integrated circuit for tv and monitor applications", IEEE TRANSACTIONS ON CONSUMER ELECTRONICS, vol. 36, no. 1, February 1990 (1990-02-01), NEW YORK US, pages 10 - 17, XP000103534, DOI: doi:10.1109/30.46604

Cited by

EP1755335A1; KR100427156B1; DE10016859B4; DE10016859B8; US7375991B2; US6538419B1

Designated contracting state (EPC)

DE ES FR GB IT

DOCDB simple family (publication)

EP 0521419 A2 19930107; **EP 0521419 A3 19950111**; **EP 0521419 B1 19981223**; DE 69227949 D1 19990204; DE 69227949 T2 19990527; ES 2125875 T3 19990316; GB 9114354 D0 19910821; JP 3537457 B2 20040614; JP H05227499 A 19930903; KR 100264823 B1 20000901; KR 930003711 A 19930224; SG 67929 A1 19991019; US 5270823 A 19931214

DOCDB simple family (application)

EP 92110911 A 19920627; DE 69227949 T 19920627; ES 92110911 T 19920627; GB 9114354 A 19910703; JP 20039892 A 19920703; KR 920011912 A 19920703; SG 1996008448 A 19920627; US 90687292 A 19920702