

Title (en)

Defect indicator for arrester.

Title (de)

Fehleranzeige für einen Blitzableiter.

Title (fr)

Indicateur de défaut pour un parafoudre.

Publication

EP 0521805 B1 19941228 (FR)

Application

EP 92420228 A 19920702

Priority

- CH 370892 A 19921203
- CS 380792 A 19921221
- FR 9108563 A 19910703
- PT 10111492 A 19921207

Abstract (en)

[origin: EP0521805A1] It comprises two opposed electrodes (1, 2) united, on the one hand, in series by a low-voltage varistor (3) through which pass possible lightning waves and, on the other hand, in parallel via a resistor (7) which does not react during a lightning wave but rises in temperature during passing of the current generated by the grid in order to at least partly destroy a sleeve (11) surrounding the indicator. <IMAGE>

IPC 1-7

H01C 7/12; **H01T 1/12**

IPC 8 full level

G01R 31/74 (2020.01); **H01C 7/12** (2006.01); **H01T 1/12** (2006.01)

CPC (source: EP)

H01C 7/126 (2013.01); **H01T 1/12** (2013.01)

Cited by

WO9806111A1

Designated contracting state (EPC)

BE DE ES FR GB IT

DOCDB simple family (publication)

EP 0521805 A1 19930107; **EP 0521805 B1 19941228**; CH 687486 A5 19961213; CZ 282376 B6 19970716; CZ 380792 A3 19940713; DE 69201021 D1 19950209; DE 69201021 T2 19950524; ES 2066589 T3 19950301; FR 2678764 A1 19930108; FR 2678764 B1 19950210; PT 101114 A 19940729; PT 101114 B 19990930

DOCDB simple family (application)

EP 92420228 A 19920702; CH 370892 A 19921203; CS 380792 A 19921221; DE 69201021 T 19920702; ES 92420228 T 19920702; FR 9108563 A 19910703; PT 10111492 A 19921207