

Title (en)

Method and device for opening flexible articles folded off-centre.

Title (de)

Verfahren und Vorrichtung zum Oeffnen von flexiblen, aussermittig gefalteten Erzeugnissen.

Title (fr)

Procédé et dispositif pour ouvrir des articles flexibles pliés hors du centre.

Publication

EP 0522319 B1 19950201 (DE)

Application

EP 92110120 A 19920616

Priority

CH 207491 A 19910711

Abstract (en)

[origin: EP0522319A1] The folded printed products (16), which are held by clamps during folding, are fed to the opening device (24). The latter has grippers (42) with one fixed and one removable gripper jaw (52, 76), which bound a sliding gap (82) when the movable gripper jaw (76) is in the closed position. The pushing element (56) is displaceable along the sliding gap (82) in order to push the printed product (16) held in the edge region (34) by the appropriate gripper (42) out of the sliding gap (82). In this process, the pushing element (56) acts on the edge section (38) of the first part of the product (36) which projects beyond the second part of the product (40). As a result of the pre-bending of the printed products (16), the second part of the product (40) is carried along when pushed against the first part of the product (36) and is raised from the first part of the product (36) as a result of the bending as it leaves the sliding gap (82), the edge section (38) of the first part of the product (36) still being guided in the sliding gap (82). <IMAGE>

IPC 1-7

B65H 5/30

IPC 8 full level

B65H 5/30 (2006.01); **B65H 29/04** (2006.01); **B65H 39/065** (2006.01)

CPC (source: EP US)

B65H 5/308 (2013.01 - EP US); **B65H 2301/323** (2013.01 - EP US)

Cited by

EP0647582A1; US5697607A; WO0164560A1

Designated contracting state (EPC)

CH DE GB LI SE

DOCDB simple family (publication)

EP 0522319 A1 19930113; EP 0522319 B1 19950201; DE 59201323 D1 19950316; JP 2534601 B2 19960918; JP H05213479 A 19930824; US 5248135 A 19930928

DOCDB simple family (application)

EP 92110120 A 19920616; DE 59201323 T 19920616; JP 20730592 A 19920710; US 91069292 A 19920708