

Title (en)

Device for pickproofing combination locks.

Title (de)

Abtastsicherung für ein Kombinationsschloss.

Title (fr)

Moyens anti crocheting pour serrure à combinaison.

Publication

EP 0523262 A1 19930120 (EN)

Application

EP 91111767 A 19910715

Priority

EP 91111767 A 19910715

Abstract (en)

A mechanism for preventing picking of a combination lock comprises a sensor 11 for sensing the number of revolutions or partial revolutions of the shaft 4 of the combination lock within a given time period. The combination shaft 4 of the lock is provided with a toothed or cammed wheel and with a pivotably mounted lever arm 6. A first free end 8 of the arm is adapted to engage the toothed or cammed wheel 5 and a second end thereof is movable through the selectively applied attraction from an electromagnet 10 to lock the combination shaft 4 when it is determined that the combination wheel is being tampered with. <IMAGE> <IMAGE>

IPC 1-7

E05B 37/00; E05B 37/08

IPC 8 full level

E05B 37/00 (2006.01)

CPC (source: EP)

E05B 37/00 (2013.01)

Citation (search report)

- [X] EP 0361881 A2 19900404 - C & M TECHNOLOGY INC [US]
- [A] EP 0371701 A1 19900606 - YALE SECURITY PROD LTD [GB]
- [A] DE 3700891 A1 19870619 - GECO SICHERUNGSTECHNIK [DE]

Cited by

WO2007095652A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0523262 A1 19930120

DOCDB simple family (application)

EP 91111767 A 19910715