

Title (en)

Method and apparatus for preventing marks on textile tubular materials

Title (de)

Verfahren zur Vermeidung von Bugmarkierungen in Schlauch-Wirkware und Vorrichtung zur Durchführung des Verfahrens

Title (fr)

Procédé et appareil pour éviter des marques sur des matériaux tubulaires textiles

Publication

EP 0523419 B1 19961009 (DE)

Application

EP 92110707 A 19920625

Priority

DE 4123477 A 19910716

Abstract (en)

[origin: EP0523419A1] The tubular knitted fabric is guided by way of a first rotatably designed system of pairs of squeeze rollers and, with the fabric being drawn off continuously at the same time, is squeezed all-round by a second system of squeeze rollers which cooperates with the first system. The possibility that crease markings will occur is thus completely prevented. The squeezing apparatus consists of an externally held rotatably arranged first system of pairs of squeeze rollers which has an adjustable outer circumference and of an externally held rotatably arranged second squeeze-roller system which is matched to the circumference of the first system of pairs of squeeze rollers and which is connected operatively to the first system. <IMAGE>

IPC 1-7

D06B 15/02

IPC 8 full level

D06B 15/02 (2006.01); **D06C 15/02** (2006.01); **D06C 29/00** (2006.01)

CPC (source: EP US)

D06B 15/025 (2013.01 - EP US)

Cited by

CN102587054A

Designated contracting state (EPC)

CH DE FR GB IT LI

DOCDB simple family (publication)

EP 0523419 A1 19930120; EP 0523419 B1 19961009; DE 4123477 A1 19930121; DE 4123477 C2 19940825; DE 59207317 D1 19961114; JP 2624425 B2 19970625; JP H05272054 A 19931019; US 5279023 A 19940118

DOCDB simple family (application)

EP 92110707 A 19920625; DE 4123477 A 19910716; DE 59207317 T 19920625; JP 18825792 A 19920715; US 91500592 A 19920716