

Title (en)

Method and punch for deep-drawing containers with a continuous wall.

Title (de)

Verfahren und Stempel für das Tiefziehen von Behältern mit regelmässiger Wandung.

Title (fr)

Procédé et poinçon d'emboutissage pour la fabrication de récipients à paroi régulière.

Publication

EP 0524098 B1 19950222 (FR)

Application

EP 92402056 A 19920716

Priority

FR 9109053 A 19910717

Abstract (en)

[origin: EP0524098A1] The invention relates to a method for deep-drawing blanks of flat metal products having undergone a drawing or rolling operation, with a view to carrying out subsequent deep-redrawing or repeated-passing operations or with a view to manufacturing flanged containers, in particular cylindrical containers, characterised in that a punch is used whose tip has a variable transition (coupling) radius which is determined as a function of the anisotropic characteristics of the blank material. Advantageously the next step is an operation for grinding the bottom of the container by using a punch having a constant transition (coupling) radius. Application to the manufacture of metal tumblers. <IMAGE>

IPC 1-7

B21D 22/20

IPC 8 full level

B21D 22/20 (2006.01)

CPC (source: EP)

B21D 22/20 (2013.01)

Cited by

US5950858A; DE102011077328A1; EP0629009A1; US5576113A; US5603782A; US5840441A; WO9419246A3

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU NL PT SE

DOCDB simple family (publication)

EP 0524098 A1 19930120; EP 0524098 B1 19950222; AT E118705 T1 19950315; DE 69201465 D1 19950330; DE 69201465 T2 19950713; DK 0524098 T3 19950731; ES 2070605 T3 19950601; FR 2679158 A1 19930122; FR 2679158 B1 19950721

DOCDB simple family (application)

EP 92402056 A 19920716; AT 92402056 T 19920716; DE 69201465 T 19920716; DK 92402056 T 19920716; ES 92402056 T 19920716; FR 9109053 A 19910717