

Title (en)
Wrenching tool.

Title (de)
Schraubenschlüssel.

Title (fr)
Clé de serrage.

Publication
EP 0525356 A1 19930203 (EN)

Application
EP 92110087 A 19861216

Priority
• CA 542405 A 19870717
• EP 86309812 A 19861216
• US 81025385 A 19851218

Abstract (en)
A rotary wrenching tool having an opening for receiving a polygonal head of a threaded member is sized to receive the heads of threaded members that are themselves sized in at least two different nominal sizes such that the ratio of the maximum and minimum of those nominal sizes lies in the range from 1.0053 to 1.1430 for square heads and from 1.0053 to 1.0600 for hexagonal heads, the tool bearing visible markings, preferably adjacent the opening of the tool, identifying said at least two nominal sizes. In a preferred form the visible markings identifying the at least two nominal sizes relate to nominal sizes in at least two different sizing systems, for example in metric, United States Standards or British Standard. <IMAGE>

IPC 1-7
B25B 13/04; B25B 13/48

IPC 8 full level
B25B 13/04 (2006.01); **B25B 13/06** (2006.01)

CPC (source: EP)
B25B 13/04 (2013.01); **B25B 13/065** (2013.01)

Citation (search report)
• [A] GB 1464808 A 19770216 - TIN WAH CHEUNG
• [AD] US 4100824 A 19780718 - MARSCHKE JON V
• [A] EP 0156681 A1 19851002 - FACOM [FR]
• [A] US 4512220 A 19850423 - BARNHILL III MARTIN L [US], et al
• [A] DE 1088437 B 19600901 - FRITZ DIEBOLD

Cited by
FR2714321A1; EP4311628A3; GB2624052A

Designated contracting state (EPC)
AT CH DE FR GB IT LI SE

DOCDB simple family (publication)
EP 0236630 A1 19870916; EP 0236630 B1 19940907; AT E111006 T1 19940915; CA 1327464 C 19940308; DE 3650060 D1 19941013; DE 3650060 T2 19950302; EP 0525356 A1 19930203; EP 0525356 B1 19981021

DOCDB simple family (application)
EP 86309812 A 19861216; AT 86309812 T 19861216; CA 542405 A 19870717; DE 3650060 T 19861216; EP 92110087 A 19861216