

Title (en)

Single-use injection nozzle for straw filling machine, especially for artificial insemination of animals and conservation of biological products

Title (de)

Einwegspritzdüse für Anfüllungsmaschine von Röhrchen, besonders für künstliche Besamung und um biologische Produkte aufzubewahren

Title (fr)

Buse d'injection à usage unique pour machine de remplissage de paillettes, notamment pour l'insémination artificielle d'animaux et conservation de produits biologiques

Publication

EP 0527676 B1 19951213 (FR)

Application

EP 92402245 A 19920806

Priority

FR 9110032 A 19910807

Abstract (en)

[origin: EP0527676A1] Conventionally, straws (1) are filled by suction through a suction nozzle (2), fitted with a needle (22) which penetrates into the straw behind a composite plug (11) and is fitted with a seal (23). A biological product (diluted sperm) (37) rises through a flexible pipe (34) made of elastomer towards an injection nozzle (3) in response to the reduced pressure in the straw (1). The flexible pipe (34) is held centred over at least five times its external diameter, in a hoop (31,32) held in a support. The elastomer which constitutes the flexible pipe (34) has a Shore hardness of 41 to 47, and a capacity for reversible extension of at least 250 %. These devices ensure strict centring of the needle (33) in the hoop (31, 32) despite the flexibility of the pipe. The parts which have been in contact with the sperm may be disposed of after one ejaculation has been exhausted, instead of requiring expensive cleaning operations. <IMAGE>

IPC 1-7

A61D 19/02

IPC 8 full level

A61D 19/02 (2006.01)

CPC (source: EP US)

A61D 19/024 (2013.01 - EP US); **Y10S 604/905** (2013.01 - EP US)

Designated contracting state (EPC)

CH DE DK GB IT LI NL

DOCDB simple family (publication)

EP 0527676 A1 19930217; EP 0527676 B1 19951213; DE 69206714 D1 19960125; DE 69206714 T2 19960502; DK 0527676 T3 19960429; FR 2680101 A1 19930212; FR 2680101 B1 19931105; US 5249610 A 19931005

DOCDB simple family (application)

EP 92402245 A 19920806; DE 69206714 T 19920806; DK 92402245 T 19920806; FR 9110032 A 19910807; US 92586592 A 19920807