

Title (en)
CHUCK FOR MACHINE TOOLS

Publication
EP 0528155 A3 19930728 (DE)

Application
EP 92111323 A 19920703

Priority
CH 243391 A 19910819

Abstract (en)
[origin: EP0528155A2] A hydraulic piston (6) having fastening bolts (5) attached to it is provided in the basic chuck (1) and is movable axially to the rotational axis of the machine tool. The spring-actuated fastening chuck (13) is fastened in an axially displaceable manner to the end of the fastening bolt (5). Hydraulic pistons (10) having forcing bolts (9) attached to them are likewise provided in the basic chuck, one piston side of which hydraulic pistons (10) is connected together with one side of the piston (6) of the fastening bolt (5). By hydraulic pressing of the two pistons (6, 10) against one another, the clamping part of the fastening chuck (13) is pressed against the main body and releases the workpiece (3), the fastening chuck (13) remaining axially movable. Consequently, movements between the workpiece (3) and the fastening chuck (13) do not lead to the lifting of the workpiece (3) from the centring arbor (2). <IMAGE>

IPC 1-7
B23B 31/16

IPC 8 full level
B23B 31/173 (2006.01); **B23B 33/00** (2006.01)

CPC (source: EP)
B23B 31/16179 (2013.01); **B23B 31/16187** (2013.01); **B23B 33/00** (2013.01)

Citation (search report)
• [A] US 2948540 A 19600809 - GARBERDING WALDO L, et al
• [A] EP 0186107 A2 19860702 - FUJITSU LTD [JP]

Cited by
CN111571372A; CN115780849A; CN108500309A; CN115156964A; CN111037493A; CN109227442A

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0528155 A2 19930224; EP 0528155 A3 19930728

DOCDB simple family (application)
EP 92111323 A 19920703