

Title (en)
Self-stripping contact

Title (de)
Abisolierfreier Kontakt

Title (fr)
Contact autodénudant

Publication
EP 0532413 B1 19960710 (FR)

Application
EP 92402465 A 19920909

Priority
FR 9111268 A 19910912

Abstract (en)
[origin: EP0532413A1] The insulation-displacement (self-stripping) contact is constituted by a conducting blade having two elastic arms bounded on either side of a slit emerging at a first of its ends in an inlet for an insulated conductor. It is characterised in that it includes a single rectangular piercing (punching) member (7) on the said two elastic arms (3, 4), substantially on the first end of the slit (2) but not contiguous with the said inlet (5) for an insulated conductor. <IMAGE>

IPC 1-7
H01R 4/24

IPC 8 full level
H01R 4/24 (2006.01)

CPC (source: EP)
H01R 4/2425 (2013.01)

Cited by
EP0698941A1; US5833487A; US6776647B1; WO0069024A1

Designated contracting state (EPC)
DE FR GB IT SE

DOCDB simple family (publication)
EP 0532413 A1 19930317; EP 0532413 B1 19960710; DE 69212090 D1 19960814; DE 69212090 T2 19961107; FR 2681477 A1 19930319; FR 2681477 B1 19950623

DOCDB simple family (application)
EP 92402465 A 19920909; DE 69212090 T 19920909; FR 9111268 A 19910912