

Title (en)  
Hydrostatic machine with drainage for leaking oil

Title (de)  
Hydrostatische Maschine mit Leckölabführung

Title (fr)  
Machine hydrostatique avec drainage d'huile de fuite

Publication  
**EP 0534067 B1 19971022 (DE)**

Application  
**EP 92110949 A 19920629**

Priority  
DE 4128615 A 19910828

Abstract (en)  
[origin: EP0534067A2] The invention relates to a hydrostatic machine, especially an axial piston machine, having a casing whose interior accommodates a driving mechanism and comprises a leaked-oil chamber which receives leaked oil and is connected to the tank via a leaked-oil connection. In order to avoid splash losses of the hydrostatic machine, a pumping appliance (34; 50, 51; 50, 56) for stripping leaked oil from the leaked-oil chamber (29) is disposed between the leaked-oil connection (30) and the tank (9). <IMAGE>

IPC 1-7  
**F04B 53/00**; **F04B 1/12**; **F16H 61/42**

IPC 8 full level  
**F03C 1/253** (2006.01); **F03C 1/40** (2006.01); **F04B 1/12** (2006.01); **F04B 1/20** (2006.01); **F04B 1/24** (2006.01); **F04B 1/26** (2006.01); **F04B 49/00** (2006.01); **F04B 53/00** (2006.01); **F04B 53/04** (2006.01); **F16H 61/42** (2006.01)

CPC (source: EP)  
**F04B 53/04** (2013.01)

Cited by  
EP3745002A1; EP1308620A1; DE202008001060U1; EP1990100A1; DE202019005783U1; US6865980B2; US6755018B2; US7980788B2; DE102012012973A1; WO0165113A1; EP3650693A1; IT201800010097A1

Designated contracting state (EPC)  
DE FR GB IT SE

DOCDB simple family (publication)  
**DE 4128615 C1 19930114**; DE 59208983 D1 19971127; EP 0534067 A2 19930331; EP 0534067 A3 19940525; EP 0534067 B1 19971022; JP 3485585 B2 20040113; JP H05202842 A 19930810

DOCDB simple family (application)  
**DE 4128615 A 19910828**; DE 59208983 T 19920629; EP 92110949 A 19920629; JP 22868192 A 19920827