

Title (en)

Shroud band for axial flow turbine.

Title (de)

Deckband für axialdurchströmte Turbine.

Title (fr)

Bande de recouvrement pour roue de turbine axiale.

Publication

**EP 0536575 B1 19950405 (DE)**

Application

**EP 92116009 A 19920918**

Priority

CH 296591 A 19911008

Abstract (en)

[origin: JPH05195988A] PURPOSE: To provide circumferential shroud plates that can guarantee smooth guidance of a main flow without separation and achieve a good sealing action in addition to a good sealing action. CONSTITUTION: In a device for sealing a gap between rotor blades 6 and a casing 2 of a turbomachine, the rotor blades 6 are provided with ring-shaped circumferential shroud plates 11 which seal by a plurality of serrations 12-15 against the casing 2 with the formation of radial gaps 16-18, and the casing 2 is configured with a conical profile 28. Further, the shroud plate 11, which is arranged at the end of the blade, has four throttle locations relative to the casing, and the inlet end throttle location forms a diagonal gap 19 in a stationary operation state.

IPC 1-7

**F01D 11/08**; **F01D 5/20**

IPC 8 full level

**F04D 29/08** (2006.01); **F01D 5/20** (2006.01); **F01D 5/22** (2006.01); **F01D 11/08** (2006.01); **F01D 11/12** (2006.01)

CPC (source: EP US)

**F01D 5/225** (2013.01 - EP US); **F01D 11/08** (2013.01 - EP US); **F01D 11/12** (2013.01 - EP US)

Cited by

EP1267042A3; EP2280149A1; EP2551460A1; CN103184900A; KR20200126773A; EP0903468A1; US6102655A; EP3399152A3; WO2009138057A3

Designated contracting state (EPC)

CH DE FR GB IT LI NL

DOCDB simple family (publication)

**EP 0536575 A1 19930414**; **EP 0536575 B1 19950405**; DE 59201833 D1 19950511; JP 3307692 B2 20020724; JP H05195988 A 19930806; PL 296074 A1 19930517; US 5290144 A 19940301

DOCDB simple family (application)

**EP 92116009 A 19920918**; DE 59201833 T 19920918; JP 26836992 A 19921007; PL 29607492 A 19920928; US 95183992 A 19920928