

Title (en)

SPARK PLUG FOR INTERNAL COMBUSTION ENGINE

Title (de)

ZÜNDKERZE FÜR BRENNKRAFTMASCHINE

Title (fr)

BOUGIE D'ALLUMAGE POUR MOTEUR A COMBUSTION INTERNE

Publication

EP 0537156 B1 19960703 (EN)

Application

EP 91907630 A 19910402

Priority

- GB 9007659 A 19900404
- US 9102239 W 19910402

Abstract (en)

[origin: GB2242703A] The spark plug comprises an outer shell (1), a central electrode (2), an insulator (3) surrounding the central electrode (2) and at least one ground electrode (4B) connected at at least one point to the outer shell (1). At least one (4B) of the electrodes consists of an outer layer made of a corrosion resistant material (e.g. nickel or a nickel alloy) and of an inner core made of a material having good thermal conductivity characteristics and a good corrosion and erosion resistance (e.g. silver or a silver alloy). In front of the bottom end of the other electrode (2), i.e. at the spark gap (5) the inner core projects through the outer layer perpendicularly to the longitudinal axis of said one electrode (4B). Several embodiments of the spark plug as well as several methods for making the electrodes of the spark plug are described.

IPC 1-7

H01T 13/20; H01T 13/32; H01T 21/02; H01T 13/39

IPC 8 full level

H01T 13/32 (2006.01); **H01T 13/39** (2006.01); **H01T 21/02** (2006.01)

CPC (source: EP)

H01T 13/32 (2013.01); **H01T 13/39** (2013.01); **H01T 21/02** (2013.01)

Cited by

GB2242703B

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

WO 9115887 A1 19911017; AT E140107 T1 19960715; AU 7682291 A 19911030; DE 69120677 D1 19960808; DE 69120677 T2 19961212;
EP 0537156 A1 19930421; EP 0537156 A4 19940427; EP 0537156 B1 19960703; GB 2242703 A 19911009; GB 2242703 B 19940216;
GB 9007659 D0 19900530

DOCDB simple family (application)

US 9102239 W 19910402; AT 91907630 T 19910402; AU 7682291 A 19910402; DE 69120677 T 19910402; EP 91907630 A 19910402;
GB 9007659 A 19900404