

Title (en)

Device for automatic coupling a metallurgical ladle to conduits

Title (de)

Vorrichtung zum automatischen Ankuppeln von Versorgungsleitungen an ein metallurgisches Gefäß

Title (fr)

Dispositif d'accouplement automatique d'une poche métallurgique à des conduites

Publication

EP 0537536 B1 19961113 (FR)

Application

EP 92116524 A 19920928

Priority

LU 88014 A 19911009

Abstract (en)

[origin: EP0537536A1] Device for automatic coupling between conduits on a metallurgical treatment station (2) and conduits on a metallurgical ladle (1). The half-coupling (4) associated with the treatment station is supported by a movable element and is kept in a protected stand-by position on the station (2) in order to be automatically positioned by first means in a coupling position with the half-coupling (5) associated with the ladle (1) just before deposition of the ladle (1) on its seat (3) provided on the station (2). Second means bring the movable element supporting the half-coupling (4) back into the protected stand-by position at the moment when the ladle (1) is withdrawn from its seat. <IMAGE>

IPC 1-7

B22D 1/00; C21C 7/072

IPC 8 full level

B22D 1/00 (2006.01); **C21C 5/46** (2006.01)

CPC (source: EP)

B22D 1/00 (2013.01); **B22D 1/005** (2013.01); **C21C 5/462** (2013.01)

Cited by

LU90564B1; EP0729797A1; US5823221A; EP0666324A1; US5520374A; WO0179566A1

Designated contracting state (EPC)

AT BE CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0537536 A1 19930421; EP 0537536 B1 19961113; AT E145161 T1 19961115; DE 69215190 D1 19961219; DE 69215190 T2 19970515; ES 2095996 T3 19970301; LU 88014 A1 19930517

DOCDB simple family (application)

EP 92116524 A 19920928; AT 92116524 T 19920928; DE 69215190 T 19920928; ES 92116524 T 19920928; LU 88014 A 19911009